HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier Assault XL

Other means of identification

SDS number 587N-083J
Product code HIL00151
Recommended use Stripper

Recommended restrictions For Labeled Use Only **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer

Company name HILLYARD INDUSTRIES
Address 302 North Fourth St.
St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (800) 365-1555 (Ext. 8206)

Fax (816) 383-8406

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

involving chemicals)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 3

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory

irritation. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Avoid release to the environment. Wear protective gloves/protective

clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Material name: Assault XL SDS US

Disposal

Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanolamine		141-43-5	10 - < 20
Benzyl Alcohol		100-51-6	5 - < 10
Sodium Hydroxide		1310-73-2	3 - < 5
Other components below re		70 - < 80	

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact

Ingestion

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Assault XL SDS US 2/8

Methods and materials for containment and cleaning up

The product is completely soluble in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid breathing mist/vapors. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Expo Components	sure Limits (PEL) for Air Co Type	ntaminants (29 CFR 1910.1000) Value	
Ethanolamine (CAS 141-43-5)	PEL	6 mg/m3	
		3 ppm	
Sodium Hydroxide (CAS 1310-73-2)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Values (TI	LV)		
Components	Туре	Value	
Ethanolamine (CAS 141-43-5)	STEL	6 ppm	
	TWA	3 ppm	
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
NIOSH. Immediately Dangerous to Life	e or Health (IDLH) Values, as	amended	
Components	Туре	Value	
Ethanolamine (CAS 141-43-5)	IDLH	3 %	
		30 ppm	
Sodium Hydroxide (CAS 1310-73-2)	IDLH	10 mg/m3	
US. NIOSH: Pocket Guide to Chemical			
Components	Туре	Value	
Ethanolamine (CAS 141-43-5)	STEL	15 mg/m3	
		6 ppm	
	TWA	8 mg/m3	
		3 ppm	
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
US. OARS. Workplace Environmental	Exposure Level (WEEL) Gui	de	
Components	Туре	Value	
Benzyl Alcohol (CAS 100-51-6)	TWA	44.2 mg/m3	

Material name: Assault XL SDS US 3/8

Value Components Type

10 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Avoid contact with eyes. Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Chemical safety goggles when working with concentrate.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

Chemical respirator with organic vapor cartridge and full facepiece. Not normally required with Respiratory protection

adequate ventilation.

Thermal hazards None known. Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear, pale yellow liquid

Physical state Liquid. Liquid. Form Color Pale yellow

Non-objectional odor. Odor

Odor threshold Not available. > 13 - < 14

Not applicable / Not available Melting point/freezing point

Initial boiling point and boiling

range

205 °F (96.11 °C)

>200.0 °F (>93.3 °C) Tag Closed Cup Flash point

<1 Ethyl ether = 1 **Evaporation rate** Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available. 16.71 mm Hg Vapor pressure 1.039 Air=1 Vapor density Relative density 1.002

Solubility(ies)

100 % Complete Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available Not available. **Decomposition temperature** Not available. Viscosity

Other information

8.83 lbs/gal Density **Explosive properties** Not explosive. Not oxidizing. Oxidizing properties > 91 - < 93 % Percent volatile

Material name: Assault XL SDS US VOC 6.8 %

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not mix with Conditions to avoid

other chemicals.

Strong acids. Strong oxidizing agents. Oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Causes serious eye damage. Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

140 - 340 mg/kg

blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results	
Benzyl Alcohol (CAS 100-51-6)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	2000 mg/kg	
Inhalation			
LC50	Rat	> 4.178 mg/l, 4 Hours	
Oral			
LD50	Rat	1230 - 3100 mg/kg	
Ethanolamine (CAS 141-43-5)			
<u>Acute</u>			
Dermal			
LD50	Rat	1 g/kg	
Sodium Hydroxide (CAS 1310-73-2	2)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	1350 mg/kg	

Rat Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

Oral LD50

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

Material name: Assault XL SDS US 5/8

HIL00151 Version #: 01 Issue date: 01-12-2024

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Product		Species	Test Results
Assault XL			
Aquatic			
Crustacea	EC50	Daphnia	768.6667 mg/l, 48 hours estimated
Fish	LC50	Fish	2777.7778 mg/l, 96 hours estimated
Acute			
Crustacea	EC50	Daphnia	383.8583 mg/l, 48 hours estimated
Fish	LC50	Fish	118.5191 mg/l, 96 hours estimated
Components		Species	Test Results
Benzyl Alcohol (CAS 1	100-51-6)		
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	10 mg/l, 96 hours
Ethanolamine (CAS 1	41-43-5)		
Aquatic			
Acute			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	114 - 196 mg/l, 96 hours
Sodium Hydroxide (CA	AS 1310-73-2)		
Aquatic			
Acute			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours
Fish	LC50	Western mosquitofish (Gambusia affinis) 125 mg/l, 96 hours	

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl Alcohol 1.1 Ethanolamine -1.31

Mobility in soil This product is completely water soluble and will disperse in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Material name: Assault XL sps us

HIL00151 Version #: 01 Issue date: 01-12-2024

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Incinerate

the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical

or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

D002: Waste Corrosive material [pH ≤2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not established.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory

or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Sodium Hydroxide (CAS 1310-73-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Skin corrosion or irritation

categories

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Material name: Assault XL SDS US 7/8

HIL00151 Version #: 01 Issue date: 01-12-2024

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Sodium Hydroxide (CAS 1310-73-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information, including date of preparation or last revision

Issue date 01-12-2024

Version # 01

HMIS® ratings Health: 3

Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Material name: Assault XL SDS US

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).