

Version 1.1	SDS Number: 400000000442	Revision Date: 08/02/2020

SECTION 1. IDENTIFICATION

Product name	:	PURELL® Advanced Hand Sanitizer Foam
Manufacturer or supplier's d	eta	ills
Company name of supplier Address		GOJO Industries, Inc. One GOJO Plaza, Suite 500 Akron, Ohio 44311
Telephone	:	1 (330) 255-6000
Emergency telephone number	:	CHEMTREC 1-800-424-9300 CHEMTREC +1-703-527-3887: Outside USA & CANADA

Recommended use of the chemical and restrictions on use

Recommended use	: Hand Sanitizer
Restrictions on use	: This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information provided on the package or instruction sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Eye irritation	: Category 2A
GHS label elements Hazard pictograms	
Signal word	: Warning
Hazard statements	 H226 Flammable liquid and vapour. H319 Causes serious eye irritation.
Precautionary statements	 Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 Keep container tightly closed.



ersion 1.1	SDS Number: 40000000442	Revision Date: 08/02/2020
	 P240 Ground/bond container a P241 Use explosion-proof elect equipment. P242 Use only non-sparking to P243 Take precautionary meas P280 Wear eye protection/ face Response: P305 + P351 + P338 IF IN EYE for several minutes. Remove co to do. Continue rinsing. P337 + P313 If eye irritation pe attention. P370 + P378 In case of fire: Us alcohol-resistant foam to exting Storage: P403 + P235 Store in a well-ve Disposal: P501 Dispose of contents/ cont disposal plant. 	trical/ ventilating/ lighting/ ols. sures against static discharge. e protection. ES: Rinse cautiously with water ontact lenses, if present and eas ersists: Get medical advice/ se dry sand, dry chemical or guish. entilated place. Keep cool.

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Ethyl Alcohol	64-17-5	>= 60 - < 70
Isopropyl Alcohol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	 In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. If symptoms persist, call a physician.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if irritation develops and persists.
In case of eye contact	 In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Seek medical advice.
If swallowed	: Do NOT induce vomiting. Rinse mouth with water. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: Causes serious eye irritation.
Protection of first-aiders	: First Aid responders should pay attention to self-protection and use the recommended protective clothing



 Version 1.1
 SDS Number: 40000000442
 Revision Date: 08/02/2020

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not use a solid water stream as it may scatter and spread fire. Cool closed containers exposed to fire with water spray. Flash back possible over considerable distance. May form explosive mixtures in air. Exposure to decomposition products may be a hazard to health. Carbon oxides Silicon oxides
Hazardous combustion products	:	Carbon oxides Silicon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information		Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Material can create slippery conditions.
Environmental precautions	: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	 Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Keep in suitable, closed containers for disposal. Clean contaminated floors and objects thoroughly while observing environmental regulations.

SECTION 7. HANDLING AND STORAGE



Version 1.1	SDS Number: 400000000442	Revision Date: 08/02/2020
Advice on safe handling	: For personal protection see section Keep away from heat. Use with local exhaust ventilation Avoid contact with eyes.	
Conditions for safe storage	: Take measures to prevent the bu Keep in properly labelled containe Keep container tightly closed in a place. Store in accordance with the part	ers. dry and well-ventilated

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl Alcohol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Isopropyl Alcohol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
Isopropyl Alcohol	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection	:	No personal respiratory protective equipment normally required.
Hand protection		
Remarks	:	No special protective equipment required.
Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	No special measures necessary provided product is used correctly.
Protective measures	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Ensure that eye flushing systems and safety showers are located close to the working place.



Version 1.1	SDS Number: 400000000442	Revision Date: 08/02/2020
Hygiene measures	: Handle in accordance with goo practice. Avoid contact with eyes.	d industrial hygiene and safety

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colour Odour Odour Threshold	 liquid clear, colourless, yellow like fruit No data available 	
рН	: 6 - 9, (20 °C)	
Melting point/freezing point Initial boiling point and boiling range	: No data available : 74.00 °C	
Flash point	: 27.00 °C	
Evaporation rate	: No data available	
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: No data available	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 0.8730 g/cm3	
Solubility(ies) Water solubility	: soluble	
Partition coefficient: n- octanol/water	: Not applicable	
Auto-ignition temperature	: No data available	
Thermal decomposition	: The substance or mixture is not classified self-reactive.	
Viscosity Viscosity, kinematic	: 10 - 20 mm2/s (20 °C)	
Explosive properties	: Not explosive	
Oxidizing properties	: The substance or mixture is not classified as oxidizing.	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.



Version 1.1	SDS Number: 400000000442	Revision Date: 08/02/2020
Possibility of hazardous reactions	: Vapours may form explosive m	nixture with air.
Conditions to avoid Incompatible materials	 Heat, flames and sparks. Strong oxidizing agents Flammable solids Water-reactive substances 	
Hazardous decomposition products	: No hazardous decomposition p	products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Inhalation Eye contact Skin contact			
Acute toxicity Not classified based on available information.			
<u>Components:</u> Ethyl Alcohol: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg		
Acute inhalation toxicity	: LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapour		
Isopropyl Alcohol:			
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg		
Acute inhalation toxicity	: LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapour		
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg		

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethyl Alcohol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Isopropyl Alcohol:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethyl Alcohol: Species: Rabbit



Version 1.1

SDS Number: 40000000442

Revision Date: 08/02/2020

Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

Isopropyl Alcohol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

Ethyl Alcohol:

Test Type: Local lymph node assay (LLNA) Exposure routes: Skin contact Species: Mouse Result: negative

Isopropyl Alcohol:

Test Type: Buehler Test Exposure routes: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethyl Alcohol:	
Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	 Test Type: Rodent dominant lethal test (germ cell) (in vivo) Test species: Mouse Application Route: Ingestion Result: negative
Isopropyl Alcohol:	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Test species: Mouse
	Application Route: Intraperitoneal injection
	Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Isopropyl Alcohol: Species: Rat



Version 1.1	SDS Number: 400000000442	Revision Date: 08/02/2020	
Application Route: inhalation (vapour) Exposure time: 104 weeks Method: OECD Test Guideline 451 Result: negative			
IARC	No component of this product presen equal to 0.1% is identified as probably human carcinogen by IARC.		
OSHA	No component of this product presen equal to 0.1% is identified as a carcin carcinogen by OSHA.		
NTP	No component of this product presen equal to 0.1% is identified as a known by NTP.		
Reproductive toxicity Not classified based on availa	ble information.		
Components: Ethyl Alcohol: Effects on fertility	: Test Type: Two-generation reprod Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 416 Result: negative		
Isopropyl Alcohol: Effects on fertility	: Test Type: Two-generation reprod Species: Rat Application Route: Ingestion Result: negative	uction toxicity study	
Effects on foetal development	: Test Type: Embryo-foetal develop Species: Rat Application Route: Ingestion Result: negative	ment	
STOT - single exposure			

Not classified based on available information.

Components:

Isopropyl Alcohol:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Ethyl Alcohol: Species: Rat NOAEL: 2,400 mg/kg



Version 1.1

SDS Number: 40000000442

Revision Date: 08/02/2020

Application Route: Ingestion Exposure time: 2 y

Isopropyl Alcohol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapour) Exposure time: 104 w Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethyl Alcohol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates		NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
(Chronic toxicity) Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
Isopropyl Alcohol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to bacteria	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h
Persistence and degradability		
<u>Components:</u> Ethyl Alcohol: Biodegradability	:	Result: Readily biodegradable. Biodegradation: 84 % Exposure time: 20 d

Isopropyl Alcohol:



Version 1.1	SDS Number: 40000000442	Revision Date: 08/02/2020
Biodegradability	: Result: rapidly degradable	
Bioaccumulative potential		
<u>Components:</u> Ethyl Alcohol: Partition coefficient: n- octanol/water Isopropyl Alcohol: Partition coefficient: n- octanol/water	: log Pow: -0.35 : log Pow: 0.05	
Mobility in soil No data available		
Other adverse effects No data available		
Product: Regulation	40 CFR Protection of Environm Stratospheric Ozone - CAA Se	
Remarks	This product neither contains, r Class I or Class II ODS as defin Section 602 (40 CFR 82, Subp	ned by the U.S. Clean Air Act

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from residues Contaminated packaging	 Dispose of in accordance with local regulations. Dispose of as unused product. Empty containers should be taken to an approved waste
	handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR	
UN/ID No.	: UN 1987
Proper shipping name	: Alcohols, n.o.s.
	(Ethanol, Propan-2-ol)
Class	: 3
Packing group	: 111
Packing instruction (cargo	: 366
aircraft)	
Packing instruction	: 355
(passenger aircraft)	
IMDG-Code	
UN number	: UN 1987
Proper shipping name	: ALCOHOLS, N.O.S.
	(Ethanol, Propan-2-ol)
Class	: 3



Version 1.1	SDS Number: 400000000442	Revision Date: 08/02/2020
Packing group Labels EmS Code Marine pollutant National Regulations	: III : 3 : F-E, S-D : no	
49 CFR UN/ID/NA number Proper shipping name Class Packing group ERG Code Marine pollutant	: UN 1987 : Alcohols, n.o.s. : 3 : III : 127 : no	

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

SARA 311/312 Hazards	:	Fire Hazard Acute Health Hazard		
SARA 302	:	No chemicals in this materia requirements of SARA Title		eporting
SARA 313	:	The following components are subject to reporting levels established by SARA Title III, Section 313:		
		Isopropyl Alcohol	67-63-0	3.4086 %

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

Ethyl Alcohol	64-17-5	65.2821 %
Isopropyl Alcohol	67-63-0	3.4086 %
s product does not contain a	iny VOC exemptions I	listed under the U.S. Clean Air A

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

California Prop 65	This product does not require a warning label under California
	Proposition 65.

The components of this product are reported in the following inventories:

ISCA	. Of 15CA inventory
AICS	: On the inventory, or in compliance with the inventory
DSL	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
ISHL	: On the inventory, or in compliance with the inventory




Version 1.1	SDS Number: 40000000442	Revision Date: 08/02/2020
KECI	: On the inventory, or in compliance	e with the inventory
PICCS	: On the inventory, or in compliance	e with the inventory
IECSC	: On the inventory, or in compliance	e with the inventory
NZIoC	: On the inventory, or in compliance	e with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION



Revision Date : 08/02/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.