SAFETY DATA SHEET

Innovera Duster

SECTION 1 - IDENTIFICATION

Product Name Innovera Duster

Product NumberIVR10010, IVR10012, IVR10014, IVR10016Trade Name/Chemical NameHFC-152a / Difluoroethane, R152aRecommended UseRemove dust and small particle

Restrictions On Use Read back panel on can carefully before use.

Keep out of reach of children. Misuse by deliberately concentrating and

inhaling contents may be harmful or fatal ZheJiang Ludao Technology Co., Ltd.

Product Supplied By AW Product Sales & Marketing, Inc.

Address 204, E. 2nd Avenue #343, San Mateo, CA 94401

Phone 1-415-867-7734

Emergency Phone Chemtrec 1-800-424-9300

SECTION 2 – HAZARD(S) IDENTIFICATION

Classification Flammable Gases – Category 2

Gases under pressure, Compressed gas

Signal Word Warning

Pictogram

Manufacturer



Hazard Statements Contains gas under pressure; may explode if heated.

Flammable gas

Precautionary Statements Eliminate all ignition sources if safe to do so.

Prevention Do not spray on an open flame or other ignition source. Keep away from heat Storage Store in a well-ventilated place. Do not expose to temperatures exceeding 49°C.

General Keep out of reach of children

Ingredients of

Unknown toxicity 0%

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients CAS #		% TLV PEL UNITS	
1,1-Difluoroethane	75-37-6	99.99	
Bitterant	Denatonium Benzoate	0.01	

SECTION 4 – FIRST-AID MEASURES

General Move victim to fresh air.

Give artificial respiration if victim is not breathing. Remove and isolate contaminated clothing and shoes.

In case of burns, immediately cool affected skin for as long as possible with cold water. Do not

Remove cothing if adhering to skin.

Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Eyes Flush immediately with water for at least 15 minutes. Get medical attention if ittitation occurs.

Skin Flush contaminated skin with plenty of water. Get medical attention if irritation develops.

Inhalation Remove exposed person to fresh air if adverse effects are observed.

Get immediate medical attention if respiratory, or unconsciousness occurs.

Ingestion Do not make person vomit unless directed to do so by medical personnel

Most important symptoms, acute and delayed potential acute health effects:

Eye contact Liquid can cause burns similar to frostbite.

Inhalation No known significant effects or critical hazards.

Skin contact Dermal contact with rapidly evaporating liquid could result in freezing of the tissues or frostbite.

Ingestion Ingestion of liquid can cause burns sililar to frostbite.

Note to physician: Treat symptomatically.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing media: Water spray, Water fog, Dry chemical.

Flash Point -<-50 C (<-58 F) Flammable Limits LEL - 3.9 Auto Ig. 454C UEL - 16.9

Fire and Explosion Hazards - Flammable. Cylinders are equipped with temperature and pressure relief devices but still may rupture under fire conditions. Use water spray to cool cylinders and tanks.

Special Fire Fighting Procedures - Keep container cool with water spray. If gas exiting container ignites, stop flow of gas. Do not put out the fire unless leak can be stopped immediately. Self-contained breathing apparatus (SCBA) is required if containers rupture and contents are released under fire conditions.

National Fire Protection Association (NFPA 30B) - Level 1 Aerosols (lowest flammability rating)

Consumer Products Safety Commission (CPSC 1500.3 (c)(6).16CFR - Not flammable

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Non-emergency personnel Accidental release pose a serious fire or explosion hazard. No action shall be

Taken involving any personal rish or withour suitable training. Evacuate Surrounding areas. Keep unnecessary and unprotected personnel from entering. Do you touch or walk through spilled material. Shut off all ignition sources. No Flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate Ventilation. Wear appropriate respirator when ventilation is inadequate. Put on

Appropriate personal protective equipment.

Information in Section 8 on suitable and unsuitable materials. See also the

Information in "For non-emergency personnel".

SECTION 7 – HANDLING AND STORAGE

Handling:

Keep out of reach of children. Misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Use in well ventilated area. This product can be ignited under certain circumstances. Therefore, do not use near potential ignition sources, hot surfaces, or spark-producing equipment. Do not tilt, shake, or turn can upside down before or during use as liquid contents may be dispensed. Liquid contents may cause frostbite on contact with skin. Contact physician if such contact occurs.

Storage:

Store in cool place. Do not leave in direct sunlight, enclosed vehicles, or expose to temperature above 120°F(49°C), as overheating could cause can to burst.

Note: Observe all federal, state and local regulations when storing this substance.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection Chemical type goggles or face shield optional.

Skin protection Impervious gloves should be worn.

Respiratory protection Wear breathing mask.

Ventilation No special ventilation is usually necessary. However, if operating conditions

create high air borne concentrations of this material, special ventilation may

be needed.

Other clothing and equipment: No special clothing or equipment is usually necessary.

Work practices, hygienic practices No information is available.

Protective measures during maintenance of contaminated equipment N/A

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<u>A</u>	pp	ear	an	<u>ce</u>	

Physical state	Gas [Liquefied gas]	
Color	Colorless	
Boiling Point/condensation point -25°C (-13°F)		
Melting Point	No applicable data available	
Odour	Mild	
Odour Threshold	N/A	
pH	N/A	
Flash point	[Product does not sustain combustion]	
Specific Gravity	0.91	
Percent Volatile by Volume	100 WT %	
Density	0.90 g/cc at 25°C (77°F) - Liquid	
Solubility in Water	0.28 WT% at 25°C (77°F)	
Evaporation Rate	N/A	
Decomposition Temperature	N/A	
Auto-ignition Temperature	N/A	
Vapor Pressure (MM Hg)	87 psia at 25°C (77°F)	
Vapor Density (Air=1)	2.4 at 25°C (77°F)	
Viscosity	Not applicable	

SECTION 10 – STABILITY AND REACTIVITY

Instability - Stable, however, avoid open flames and high temperatures.

Incompatibility - Incompatible with alkaline or alkaline earth metals.

Decomposition - Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and possible carbonyl fluoride.

Polymerization - Polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute toxicity N/A Irritation/Corrosion N/A

Sensitization Non-hazardous by WHMIS/OSHA criteria.

Mutagenicity N/A
Carcinogenicity N/A
Reproductive toxicity N/A
Teratogenicity N/A

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Adverse symptoms may include irritation, redness

Inhalation Adverse symptoms may include respiratory tract irritation, coughing

Skin contact Adverse symptoms may include frostbite, irritation, redness, dryness, cracking Ingestion Adverse symptoms may include frostbite, irritating to mouth, throat and stomach.

SECTION 12 - ECOLOGICAL INFORMATION

 $\begin{array}{ll} Biodegradation & N/A \\ Environmental \ fate & N/A \end{array}$

Persistence and degradability N/A Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method - Reclaim by distillation, incinerate, or remove to a permitted waste facility. Comply with Federal, State and Local regulations.

This material may be a RCRA Hazardous waste upon disposal due to the ignitability characteristic.

PPE-PERSONAL PROTECTIVE EQUIPMENT REQUIRED: NONE

SECTION 14 – TRANSPORT INFORMATION

Shipping Information

UN Number 1030

UN Proper Shipping Name 1,1-Difluoroethane

US DOT 1,1-Difluoroethane, R152a, 2.1

DOT Classification 2.1

Packing Group Not Regulated

Packaging Exceptions LTD QTY (ORM-D). AW Product Sales & Marketing, Inc. has been granted a

DOT Special Permit, SP-11516. A copy can be obtained by contacting AW

Product Sales & Marketing, Inc.

Shipping Paper Information None required

SECTION 15 – REGULATORY INFORMATION

U.S. Federal Regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA 8(1) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): This material is listed or exempted.

SARA 302 No chemicals in this material are subject to the reporting requirements of SARA

Title Ill, Section 302.

SARA 313 This material does not contain any chemical components with know CAS

number that exceed the threshold (De Minimis) reporting levels established by

SARA Title III, Section 313.

SARA 311/312 Hazards Fire Hazard, Sudden Release of Pressure Hazard

California Prop. 65 This product does not contain any chemicals known to State of California to

cause cancer, birth defects, or any other reproductive harm.

Canadian Federal Regulations This product has been classified in accordance with the hazard criteria of the

Controlled Products Regulations and the SDS contains all the information

required by the Controlled Products Regulations.

WHMIS Classification Class A: Compressed gas. Class B-1: Flammable gas

WHIMS status Controlled

Canada Domestic This product is listed on the DSL inventory list and complies with the Substances List (DSL) inventory Requirements administered by the governing country.

SECTION 16 – OTHER INFORMATION

Revised: 3/20/2020

DISCLAIMER

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.