

TECHNICAL **C**ONCEPTS

CLEAN SEAT FOAM

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 01/01/2018 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product name : CLEAN SEAT FOAM

Type of product : Detergent
Product code : RHG 5151
SKU # : FG402312

1.2. Recommended use and restrictions on use

Restrictions on use : Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

1.3. Supplier

Supplier

Rubbermaid Commercial Products LLC 3124 Valley Avenue

VA 22601-2694 Winchester - USA

T 1.800.347.9800

www.rubbermaidcommercial.com

Other

Rubbermaid Commercial Products LLC

20 Hereford Street

L6Y 0M1 Brampton - Canada

T 1.800.998.7004

1.4. Emergency telephone number

Emergency number : 24-Hour Emergency: INFOTRAC: 1-800535-5063

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable liquids, Category 3 H226 Serious eye damage/eye irritation, Category 2A H319

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA)





Signal word (GHS-CA) : Warning

Hazard statements (GHS-CA) : H226 - Flammable liquid and vapour.

H319 - Causes serious eye irritation.

Precautionary statements (GHS-CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 - Wear protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification (GHS-CA)
Alcohol	(CAS-No.) 64-17-5	30 - 60	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
ISOPROPYL ALCOHOL	(CAS-No.) 67-63-0	1 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312

05/31/2018 EN (English) Page 1

TEC402312

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Product identifier	%	Classification (GHS-CA)
PEG-40 Hydrogenated Castor Oil	(CAS-No.) 61788-85-0	< 0.1	Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse skin with water/shower.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after eye contact : Causes serious eye irritation.

Potential adverse human health effects and : Based on available data, the

symptoms

Based on available data, the classification criteria are not met.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand. Water spray.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No

smoking.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

Other information : Can be slippery on hard, smooth walking area.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static

discharge. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources,

Ignition sources.

Incompatible products : Strong bases. Strong acids.

05/31/2018 EN (English) 2/7

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ISOPROPYL ALCOHOL (67-	63-0)		
Alberta	OEL STEL (ppm)	400 ppm	
Alberta	OEL TWA (ppm)	200 ppm	
Alberta	Notations and remarks	Eye & URT irr; CNS impair	
British Columbia	OEL STEL (ppm)	400 ppm	
British Columbia	OEL TWA (ppm)	200 ppm	
British Columbia	Notations and remarks	Eye & URT irr; CNS impair	
Manitoba	OEL STEL (ppm)	400 ppm	
Manitoba	OEL TWA (ppm)	200 ppm	
New Brunswick	OEL STEL (ppm)	400 ppm	
New Brunswick	OEL TWA (ppm)	200 ppm	
New Foundland & Labrador	OEL STEL (ppm)	400 ppm	
New Foundland & Labrador	OEL TWA (ppm)	200 ppm	
Nova Scotia	OEL STEL (ppm)	400 ppm	
Nova Scotia	OEL TWA (ppm)	200 ppm	
Nunavut	OEL STEL (ppm)	400 ppm	
Nunavut	OEL TWA (ppm)	200 ppm	
Northwest Territories	OEL STEL (ppm)	400 ppm	
Northwest Territories	OEL TWA (ppm)	200 ppm	
Prince Edward Island	OEL STEL (ppm)	400 ppm	
Prince Edward Island	OEL TWA (ppm)	200 ppm	
Saskatchewan	OEL STEL (ppm)	400 ppm	
Saskatchewan	OEL TWA (ppm)	200 ppm	
Alcohol (64-17-5)			
Alberta	OEL STEL (ppm)	1000 ppm	
Alberta	Notations and remarks	URT irr	
British Columbia	OEL STEL (ppm)	1000 ppm	
British Columbia	Notations and remarks	URT irr	
Manitoba	OEL STEL (ppm)	1000 ppm	
New Brunswick	OEL STEL (ppm)	1000 ppm	
New Foundland & Labrador	OEL STEL (ppm)	1000 ppm	
Nova Scotia	OEL STEL (ppm)	1000 ppm	
Nunavut	OEL STEL (ppm)	1000 ppm	
Northwest Territories	OEL STEL (ppm)	1000 ppm	
Prince Edward Island	OEL STEL (ppm)	1000 ppm	
Saskatchewan	OEL STEL (ppm)	1250 ppm	
Ol-t-b	OFI TAVA (1000	

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

OEL TWA (ppm)

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Saskatchewan

In case of repeated or prolonged contact wear gloves

Eye protection:

05/31/2018 EN (English) 3/7

1000 ppm

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

None under normal use

Respiratory protection:

None under normal use

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid Physical state : clear. Appearance Colour : Colourless Odour : characteristic Odour threshold : No data available No data available : No data available Relative evaporation rate (butylacetate=1) Relative evaporation rate (ether=1) : No data available Melting point : No data available Freezing point : No data available : >= 78 °C

Boiling point : $>= 78 \, ^{\circ}\text{C}$ Flash point : $26 \, ^{\circ}\text{C}$

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapour.

Vapour pressure : No data available Vapour pressure at 50 °C : No data available Relative density No data available Density : 0.942 - 0.963 g/cm³ Solubility : No data available : No data available Log Pow Viscosity, kinematic : No data available **Explosive limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Chemical stability : Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

Possibility of hazardous reactions : Not established.

Conditions to avoid : Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

Incompatible materials : Strong acids. Strong bases.

Hazardous decomposition products : fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ISOPROPYL ALCOHOL (67-63-0)	
LD50 oral rat	2000 mg/kg
LD50 oral	4396 mg/kg bodyweight
LD50 dermal rat	2000 mg/kg
LD50 dermal	12800 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	46600 mg/l

05/31/2018 EN (English) 4/7

Safety Data Sheet

Respiratory or skin sensitization

according to the Hazardous Products Regulation (February 11, 2015)

Alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg
LD50 oral	10470 mg/kg bodyweight
LD50 dermal rabbit	> 16000 mg/kg
LD50 dermal	15800 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 20 mg/l/4h
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 99999 mg/l

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

: Not classified

275 mg/l

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

ISOPROPYL ALCOHOL (67-63-0)		
LC50 fish 1	100 mg/l	
EC50 Daphnia 1	100 mg/l	
EC50 other aquatic organisms 1	13299 mg/l waterflea	
EC50 other aquatic organisms 2 > 1000 mg/l		
Alcohol (64-17-5)		
LC50 fish 1	13000 mg/l	
EC50 Daphnia 1	9300 mg/l	
EC50 other aquatic organisms 1	5012 mg/l waterflea	

12.2. Persistence and degradability

EC50 other aquatic organisms 2

CLEAT CEAT I CAM		
Persistence and degradability Not established.		
Alcohol (64-17-5)		
Persistence and degradability	Not established.	

12.3. Bioaccumulative potential

CLEAN SEAT FOAM		
Bioaccumulative potential	Not established.	
ISOPROPYL ALCOHOL (67-63-0)		
Log Pow	0.05	
Alcohol (64-17-5)		
Log Pow	-0.32	
Bioaccumulative potential	Not established.	

12.4. Mobility in soil

ISOPROPYL ALCOHOL (67-63-0)	
Log Pow	0.05
Alcohol (64-17-5)	
Log Pow	-0.32

12.5. Other adverse effects

GWPmix comment	:	No known effects from this product.
Other information	:	Avoid release to the environment.

05/31/2018 EN (English) 5/7

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 13: Disposal considerations

Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Additional information Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Basic shipping description

No additional information available

Transport information/DOT

Department of Transport

DOT NA no. : UN1170 UN-No.(DOT) : 1170

Packing group (DOT) III - Minor Danger Transport document description : UN1170 Ethanol, 3, III

Proper Shipping Name (DOT) : Fthanol

Contains Statement Field Selection (DOT)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Division (DOT) : 3

Hazard labels (DOT) : 3 - Flammable liquid



: No

Dangerous for the environment

DOT Special Provisions (49 CFR 172.102)

24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized İBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242 DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

IBC code

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel. : Not applicable.

Other information : No supplementary information available.

Air and sea transport 14.3.

DOT Vessel Stowage Location

IMDG

UN-No. (IMDG) : 1170

Proper Shipping Name (IMDG) : ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

: UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, III Transport document description (IMDG)

05/31/2018 EN (English) 6/7

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

IATA

UN-No. (IATA) : 1170

Proper Shipping Name (IATA) : Ethanol solution

Transport document description (IATA) : UN 1170 Ethanol solution, 3, III

Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. National regulations

No additional information available

Alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

ISOPROPYL ALCOHOL (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

PEG-40 Hydrogenated Castor Oil (61788-85-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

Date of issue : 01/01/2018

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

SDS_CANADA_GHS_NEWELL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

05/31/2018 EN (English) 7/7