



扫二维码
关注谱尼测试



Pony Testing International Group

Report No.: MLI0IDPW31044716

SDS Report

Sample Description & Model LITHIUM-ION BATTERY 18650T22A 7S4P PACK FOR I-range S. 72.0079.2

Applicant Future Cleaning Technologies FCT BV.

Address Hoppenkuil 27A 5626 DD Eindhoven NL

No.: MLI0IDPW31044716
Code: gjp91c6n



PiaNY 谱尼测试 iit
Pony Testing International Group

www.ponytest.com	<r:lHotline 400-819-5688		
JUC:if!!!<, 1010)82618116	P:Wt; ,.E. (0431)35150908	I:itWl;!!!% (021)64851999	r:»11-J;!!! (, 10755)26050909
*.st..t%:, (, 10532J8s106866	P/th:ii<ll:!!!t,l, (0-151>ss10-16sl	Til<:liW1'<E, (0574)87736499	nw,,,:;:i:il, 1020Js9224310
.k/ll'el:l :,, (022)27360730	J,:il:l:!!! + 10-111)84650820	IA/!t,J,:;:i:, (, (0571)87219096	il:ill:l; 'i(, 1027)83997127
Illill:l;'/rar, (0991)6684186	.y.ll/tcl; :,,.d. (0371)69350670);/!t;J;!!!, (, (0512)62997900	fV:d"J;f: (, (0592)5568048



Safety Data Sheet

According to ST/SG/AC.10/30/Rev.7 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical product identification

Sample Description: LITHIUM-ION BATTERY 18650T22A 7S4P PACK FOR i-range

Sample Model: S.72.0079.2

Recommended Uses: N/A

Restrictions on use: N/A

Supplier name: Dongguan Victory Battery Technology Co., LTD

Address: Hudie NO.2 Rd, Tianxin Village, Huangjiang Town, Dongguan, Guangdong, China

Phone number: 0769-82605822

FAX: 0769-82605811

E-mail: lx@victorybattery.com.cn

Emergency phone number: 0769-82605822

Section 2 - Hazards Identification

Emergency overview: This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery.

In case of rupture: the below hazards exist.

CAS# 108-32-7
Classification according to GHS

Serious eye damage/eye irritation (2A)

Label elements

Hazard pictogram(s):
Signal word: Warning

Hazard statement(s):

H319 Causes serious eye irritation

Precautionary statement(s):



Pony Testing International Group

Prevention:

P264 Wash skin and clothing thoroughly after handling.

P280 Wear eye protection and face protection.

Response:

 P305 + P351 + P338 **F N EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

Storage

None

Disposal:

None

CAS# 105-58-8
Classification according to GHS

Flammable liquids (3)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements
Hazard pictogram(s):

Signal word: Warning

Hazard statement(s):

H226 Flammable liquid and vapour

H335 May cause respiratory irritation

Precautionary statement(s):
Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P261 Avoid breathing gas, mist, vapours and spray.

P271 Use only outdoors or in a well-ventilated area.

Response:



Pony Testing International Group

P303 + P361 + P353 **IF ON SKIN** (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P370 + P378 **In case of fire**: Use the appropriate media put out the fire.

P304 + P340 **IF INHALED**: Remove person to fresh air and keep comfortable for breathing.

P312 Call a **POISON CENTER** or doctor, if you feel unwell.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Contents handling to approved waste treatment plants.

CAS# 105-37-3

Classification according to GHS

Flammable liquids (2)

Hazardous to the aquatic environment, long-term hazard (3)

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

H225 Highly flammable liquid and vapour

H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s):

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P273 Avoid release to the environment.

Response:

P303 + P361 + P353 **IF ON SKIN** (or hair): Take off immediately all contaminated clothing.



Pony Testing International Group

Rinse skin with water.

P370 + P378 In case of fire: Use the appropriate media put out the fire.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Contents handling to approved waste treatment plants.

CAS# 7440-50-8

Classification according to GHS

Sensitisation, skin (1, 1A, 1B)

Specific target organ toxicity, single exposure (1) (digestive system)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements



Hazard pictogram(s):

Signal word: Danger

Hazard statement(s):

H317 May cause an allergic skin reaction

H370 Causes damage to organs (digestive system)

H335 May cause respiratory irritation

Precautionary statement(s):

Prevention:

P260 Do not breathe dust, fume.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, eye protection, face protection.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

Response:

P302 + P352 IF ON SKIN: Wash with plenty water.

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P321 Specific treatment (See additional emergency instructions).

P362 + P364 Take off contaminated clothing and wash it before reuse.

P308 + P311 IF exposed or concerned: Call a POISON CENTER.

P304 + P340 F INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER if you feel unwell.



Pony Testing International Group

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Contents handling to approved waste treatment plants.

CAS# 7429-90-5

Classification according to GHS

Substances and mixtures which, in contact with water, emit flammable gases (2, 3)

Specific target organ toxicity, repeated exposure (1) (respiratory system)

Label elements

Hazard pictogram(s):

Signal word: Danger

Hazard statement(s):

H261 In contact with water releases flammable gas

H372 Causes damage to organs through prolonged or repeated exposure (respiratory system)

Precautionary statement(s):

Prevention:

P223 Do not allow contact with water.

P231 + P232 Handle and store contents under inert gas, Protect from moisture.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

P260 Do not breathe dust.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Response:

P302 + P335 + P334 F ON SKIN: Brush off loose particles from skin and immerse in cool water.

P370 + P378 In case of fire: Use the appropriate media put out the fire.

P314 Get medical advice if you feel unwell.

Storage

P402 + P404 Store in a dry place. Store in a closed container.

Disposal:

P501 Contents handling to approved waste treatment plants.

Other hazards



Pony Testing International Group

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 - Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight(%)
Electrolyte/Contains Electrolyte salt and solvents	—	—	5-20
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	0.05-5
1,3-Dioxolan-2-one	96-49-1	202-510-0	5-20
1,2-Propanediolcyclic carbonate	108-32-7	203-572-1	
Diethyl carbonate	105-58-8	203-311-1	
Ethyl propionate	105-37-3	203-291-4	
Polyvinylidene fluoride resin	24937-79-9	607-458-6	<1
Copper	7440-50-8	231-159-6	3-15
Aluminium	7429-90-5	231-072-3	2-10
Cobaltate, lithium	12190-79-3	235-362-0	20-50
Graphite	7782-42-5	231-955-3	10-30

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek



medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: No data available.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment .
Such as dry powder , CO₂ .

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C(302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

Specific protective actions for fire-fighters:

Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

Section 6 - Accidental Release Measures

Personal precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

Protective equipment:

No data available.

Emergency procedures:

Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, placed the spilled material into a suitable disposal container. Keep spilled material out of sewers, ditches and bodies of water.

Environmental precautions:



扫微信二维码
关注请尼测试



Pony Testing International Group

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

All waste must refer to the United Nations, the national and local regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Consumption of food and beverage should be avoided in work areas.

Wash hands with soap and water before eating, drinking.

Ground containers when transferring liquid to prevent static accumulation and discharge.

Information about fire and explosion protection

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Conditions for safe storage, including any incompatibilities:

Requirements to be met by storerooms and receptacles

Store in a cool, dry, well-ventilated place.

Information about storage in one common storage facility

Keep away from heat, avoiding the long time of sunlight.

Further information about storage conditions

Keep container tightly sealed.

Specific and use

No data available.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
21324-40-3	N/A	N/A	N/A
96-49-1	NIA	N/A	N/A
108-32-7	N/A	N/A	N/A
105-58-8	N/A	N/A	N/A



105-37-3	N/A	N/A	N/A
24937-79-9	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m ³ TLV-TWA 1mg/m ³	REL-TWA 1mg/m ³ REL-TWA 0.1 mg/m ³	PEL-TWA 0.1 mg/m ³ PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 1mg/m ³	REL-TWA 2mg/m ³ REL-TWA 5mg/m ³ REL-TWA 10mg/m ³	PEL-TWA 5mg/m ³ PEL-TWA 15mg/m ³
12190-79-3	N/A	N/A	N/A
7782-42-5	TLV-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf PEL-TWA 20mppcf

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment

Respiratory protection: Wear suitable protective mask in order to reduce the respiratory system. A large number of leakage, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eyes Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Colour:	White.
Physical State:	Prismatic.
Odour:	Not available.
Odour threshold:	Not available.
pH:	Not available.



Pony Testing International Group

Melting point/freezing point:	Not available.
Initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.
Explosion Limits (vol% in air):	Not available.
Vapour pressure, kPa at 20°C:	Not available.
Vapor density:	Not available.
Density/Relative density (water= 1):	Not available.
Solubility(ies):	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Viscosity:	Not available.
Other information:	
Voltage	25.2V
Electric capacity	8800mAh
Electric Energy	222Wh

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatibilities materials: Oxidizing agents, acid, base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
21324-40-3	No data available.
96-49-1	LD50 Rat (oral): 10g/kg
108-32-7	LD50 Rat (oral): 2:29000mg/kg; LD50 Rabbit (Dermal): >20000mg/kg



105-58-8	No data available.
105-37-3	LD50 Rat (oral): 8732mg/kg
24937-79-9	No data available.
7440-50-8	No data available.
7429-90-5	No data available.
12190-79-3	No data available.
7782-42-5	No data available.

Skin corrosion/irritation: No data available.

Serious eye damage/irritation: No data available.

Respiratory or Skin sensitization: No data available.

Germ Cell mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive toxicity: No data available.

Specific target organ toxicity-Single exposure: No data available.

Specific target organ toxicity-Repeated exposure: No data available.

Aspiration hazard: No data available.

Information on the likely routes of exposure: No data available.

Eye: No data available.

Skin: No data available.

Ingestion: No data available.

Inhalation: No data available.

Section 12 - Ecological Information

Ecological Toxicity:

CAS# 108-32-7

LC50: >1000 mg/L- Fish (Carp)-96h;

EC50: >1000 mg/L- Crustaceans (Daphnia magna)-48h;

EC50: >900 mg/L- Algae (Scenedesmus subspicatus) -72h

Persistence and degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.



Other adverse effects: No data available.

Section 13 - Disposal Considerations

Disposal methods:

Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN Number	
IATA	UN3480
IMDG	UN3480
Model Regulation	UN3480
UN Proper shipping name	
IATA	Lithium ion batteries
IMDG	LITHIUM ION BATTERIES
Model Regulation	LITHIUM ION BATTERIES
Transport hazard class(es)	
IATA	9
IMDG	9
Model Regulation	9
Packing group	
IATA	N/A
IMDG	N/A
Model Regulation	N/A
Packaging Sign	
IATA	"-fllh.V"
IMDG	
Model Regulation	
Environmental hazards	
Marine pollutant:	No
Special precautions for user	No information available.

Transport information: The LITHIUM-ION BATTERY 18650T22A 7S4P PACK FOR i-range S.72.0079.2 has passed the test UN38.3, according to the report ID: MDIS3SKU49569721 a



131:!!!=!!!T
;(:j!!!E)!!!ut

PEJNV

Report No.: MLIOIDPW31044716 Date: 01.05.2018 Page 13 of 15

Pony Testing International Group

MDI9SEFU49568721 a,MDI9SEFU495687A21 a

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the packaging Instruction 965 section IA of IATA DGR 59th Edition for transportation. Cargo aircraft only.

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 230, 348, 384 of IMDG (38-16).

Watt-hour exceeds the standard, so it belongs to dangerous goods. The goods are packaged according to the special provision 230, 348, 384 of <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (20th).

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames. Lithium ion cells and batteries must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated capacity.

Transport Fashion: By air, by sea, by railway, by road.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
21324-40-3	Listed	Listed	Listed DSL	Listed
96-49-1	Listed	Listed	Listed DSL	Listed
108-32-7	Listed	Listed	Listed DSL	Listed
105-58-8	Listed	Listed	Listed DSL	Listed
105-37-3	Listed	Listed	Listed DSL	Listed
24937-79-9	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
12190-79-3	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed

PONY 谱尼测试
Pony Testing International Group

(l)lotline 400-819-5688 www.ponytst.com

Pony Testing Internationnl Group Shenzhen Co., Ltd.
Address: 1F., Building 6, Zhongxing Industry City, Chuangye
Road, Nanshan District, Shenzhen, Guangdong, Otino

北京分公司 (010)82618110

上海分公司 (021)64851170

天津分公司 (022)88701866

深圳分公司 (0755)26050909

广州分公司 (020)27360730

武汉分公司 (027)6930170

烟台分公司 (0531)6684186

南京分公司 (025)85376600

杭州分公司 (0571)87219091

成都分公司 (028)87736499

西安分公司 (029)89608785

昆明分公司 (0871)3451025

郑州分公司 (0371)6930170

青岛分公司 (0531)63843474

济南分公司 (0531)89224110

佛山分公司 (0757)5568048

海口分公司 (0898)87702708

重庆分公司 (023)87702708

烟台分公司 (0531)6684186



Section 16 - Other Information

Issue Time: 2018-01-05

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);

STEL: (Short Term Exposure Limit);

PEL: (Permissible Exposure Level);

REL: (Recommended Exposure Limit);

PC-STEL: (Permissible concentration-time weighted average);

PC-TWA: (Permissible concentration-short time exposure limit);

LC50: (Lethal concentration, 50 percent kill);

LOSO: (Lethal dose, 50 percent kill);

IARC: (International Agency for Research on Cancer);

EC50: (Median effective concentration);

BCF: (Bioconcentration Factor);

BOD: (Biochemical oxygen demand);

NOEC: (No observed effect concentration);

NTP: (US National Toxicology Program);

RTECS: (Registry of Toxic Effects of Chemical Substances);

IATA: (International Air Transport Association);

IMDG: (International Maritime Dangerous Goods);



扫微信二维码
关注谱尼测试



Pony Testing International Group

TOG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);

TOC: (Total Organic Carbon);

TSCA: (Toxic Substances Control Act of USA);

DSL: (the Domestic Substances List of Canada);

NDSL: (the Non-domestic Substances List of Canada)

End of report