HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier POWER-STRIP

Other means of identification

SDS number 573N-32A
Product code HIL00150
Recommended use Stripper

Recommended restrictions For Labeled Use Only

DO NOT USE ON POLISHED MARBLE.

DO NOT USE ON GLASS.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

involving chemicals)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage. Harmful to aquatic life.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection. Do not take internally.

Keep container closed when not in use.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Keep container tightly closed. Store locked up. Store away from incompatible materials.

Disposal

Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry

container for recycling or reconditioning.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Personal Protective Equipment: When there is a danger of contact with the concentrate, use

chemical safety goggles, impervious gloves, and protective clothing. Wear

impervious/slip-resistant boots such as Hillyard Stripping Boots while standing in the stripping

solution.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Sodium metasilicate		6834-92-0	5 - < 10
Ethanolamine		141-43-5	3 - < 5
Benzyl Alcohol		100-51-6	1 - < 3
Other components below re	portable levels		80 - < 90

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

blindness could result.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: POWER-STRIP SDS US

Methods and materials for containment and cleaning up

This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Air Contaminants (29 CFR 1910.1 Type	Value	
Ethanolamine (CAS 141-43-5)	PEL	6 mg/m3	
		3 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
Ethanolamine (CAS 141-43-5)	STEL	6 ppm	
	TWA	3 ppm	
US. NIOSH: Pocket Guide to Ch	nemical Hazards		
Components	Туре	Value	
Ethanolamine (CAS 141-43-5)	STEL	15 mg/m3	
,			
,		6 ppm	
,	TWA	6 ppm 8 mg/m3	
,	TWA	• •	
,	TWA Exposure Level (WEEL) Guides	8 mg/m3	
US. Workplace Environmental I		8 mg/m3	
,	Exposure Level (WEEL) Guides	8 mg/m3 3 ppm	

Biological limit values Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Material name: POWER-STRIP SDS US

Other Avoid contact with eyes, skin and clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards None known.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear, reddish brown liquid

Physical stateLiquid.FormLiquid.ColorNot available.

Odor non-objectionable odor

Odor threshold Not available pH 13 - 13.7

Melting point/freezing point Not available / Not applicable

Initial boiling point and boiling

range

205 °F (96.11 °C)

Flash point > 200.0 °F (> 93.3 °C) Tag Closed Cup

Evaporation rate < 1 Ethyl ether = 1
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 17.23 mm Hg

Vapor density 0.7567 Air=1

Relative density 1.059 at 77°F

Solubility(ies)

Solubility (water) Appreciable

Partition coefficient Not available

(n-octanol/water)

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity Not available

Other information

Density 8.82 lb/gal
Explosive properties Not explosive.
Oxidizing properties Not oxidizing.
Percent volatile 90 - 92 %
VOC 6 %

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials. Do not mix with other

chemicals.

Incompatible materials Acids. Oxidizing agents.

Hazardous decomposition No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Product

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

Test Results

blindness could result.

Species

Information on toxicological effects

Acute toxicity Not known.

POWER-STRIP		
<u>Acute</u>		
Dermal		
LD50	Rabbit	22930 mg/kg
Inhalation		
LC50	Rat	52630 mg/l, 8 Hours
Oral		
LD50	Rat	17860 mg/kg
Components	Species	Test Results

Benzyl Alcohol (CAS 100-51-6)

<u>Acute</u>

Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

Oral

LD50 Rat 1230 - 3100 mg/kg

Ethanolamine (CAS 141-43-5)

Acute Dermal

LD50 Rabbit 1025 mg/kg

Oral

LD50 Rat 10.2 g/kg

Sodium metasilicate (CAS 6834-92-0)

Acute Oral

LD50 Rat 1280 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Product		Species	Test Results
POWER-STRIP			
Aquatic			
Crustacea	EC50	Daphnia	1829.5851, 48 hours
Fish	LC50	Fish	1639.2878, 96 hours
Acute			
Crustacea	EC50	Daphnia	965.0824, 48 hours estimated
Components		Species	Test Results
Benzyl Alcohol (CAS	100-51-6)		
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	10, 96 hours

Ethanolamine (CAS 141-43-5)

Aquatic Acute

Fish LC50 Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl Alcohol 1.1 Ethanolamine -1.31

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

>= 114 - <= 196 mg/l, 96 hours

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations. Buyer assumes all risk and liability associated with

disposal of this product (original concentration or dilution) in violation of applicable law.

Local disposal regulations Dispose in a

Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <= 2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: POWER-STRIP
HIL00150 Version #: 03 Revision date: 10-25-2021 Issue date: 03-04-2015

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

UN number UN1760

UN proper shipping name Corrosive liquid, n.o.s. (Sodium metasilicate)

Transport hazard class(es)

Class 8 Subsidiary risk

Label(s) Corrosive

Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ERG number

IATA

UN1760 **UN** number

UN proper shipping name

Corrosive liquid, n.o.s. (Sodium Metasilicate)

CORROSIVE LIQUID, N.O.S. (Sodium Metasilicate)

Transport hazard class(es)

8 Class Subsidiary risk

Corrosive Label(s)

Packing group **Environmental hazards** No. **ERG Code** 154

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1760

UN proper shipping name Transport hazard class(es)

8 Subsidiary risk

Corrosive Label(s)

Packing group

Environmental hazards

Marine pollutant No. **EmS** F-A, S-B

Transport in bulk according to Annex II of MARPOL 73/78 and

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

the IBC Code

DOT



Material name: POWER-STRIP 7/9

HIL00150 Version #: 03 Revision date: 10-25-2021 Issue date: 03-04-2015

IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard

Skin corrosion or irritation

categories Serious eye damage or eye irritation

Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the or

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 03-04-2015

 Revision date
 10-25-2021

Version # 03

HMIS® ratings Health: 3

Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Revision information Product and Company Identification: MSDS Types

Hazard(s) identification: Disposal

Exposure controls/personal protection: Thermal hazards Physical & Chemical Properties: Multiple Properties Regulatory information: California Proposition 65

Material name: POWER-STRIP

HIL00150 Version #: 03 Revision date: 10-25-2021 Issue date: 03-04-2015