

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Pro Sanding Seal

Other means of identification

SDS number 583N-66D
Product code HIL00720
Recommended use Wood Floor Seal

Recommended restrictions For Labeled Use Only

Protect from Freezing

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

**Telephone number** (800) 365-1555 (Ext. 8206)

Fax (816) 383-8406

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

involving chemicals)

#### 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 5

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word Warning

**Hazard statement** May be harmful if inhaled.

Precautionary statement

**Prevention** Avoid breathing vapors. Observe good industrial hygiene practices.

Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

**Storage** Store away from incompatible materials.

**Disposal** Buyer assumes all risk and liability associated with disposal of this product (original concentration

or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry

container for recycling or reconditioning.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Dipropylene Glycol Methyl	Ether	34590-94-8	1 - < 3
Other components below re	eportable levels		90 - 100

#### 4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center or doctor/physician if you feel unwell.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical Eye contact

attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion Direct contact with eyes may cause temporary irritation.

Most important

symptoms/effects, acute and

delaved Indication of immediate

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

medical attention and special treatment needed

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions** 

# 7. Handling and storage

Precautions for safe handling

Not available.

Conditions for safe storage, including any incompatibilities Do not allow material to freeze.

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Dipropylene Glycol Methyl Ether (CAS 34590-94-8)	PEL	600 mg/m3	
		100 ppm	

**US. ACGIH Threshold Limit Values** Components Value Type Dipropylene Glycol Methyl **STEL** 150 ppm Ether (CAS 34590-94-8) **TWA** 100 ppm **US. NIOSH: Pocket Guide to Chemical Hazards** Components Value Type Dipropylene Glycol Methyl **STEL** 900 mg/m3 Ether (CAS 34590-94-8) 150 ppm **TWA** 600 mg/m3 100 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

US - California OELs: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Dipropylene Glycol Methyl Ether (CAS 34590-94-8) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Dipropylene Glycol Methyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Avoid contact with eyes. If contact is likely, safety glasses with side shields are recommended. Eye/face protection

Skin protection

Not normally needed. For prolonged or repeated skin contact use suitable protective gloves. Hand protection

None normally required. If unable to avoid prolonged or repeated contact with skin, wear Other

impervious clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards None known.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material considerations

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

## 9. Physical and chemical properties

Milky white liquid **Appearance** 

Physical state Liquid. Form Liquid. Color Milky white Mild solvent odor Odor Odor threshold Not available. 7.25 - 8.25 pН

Melting point/freezing point Not applicable / Not available

Initial boiling point and boiling > 200 °F (> 93.33 °C)

range

> 200.0 °F (> 93.3 °C) Tag Closed Cup Flash point

< 1 ethyl ether=1 **Evaporation rate** Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 17.16 mm Hg

Vapor density 1.0311 Air=1

Relative density 1.034 g/cm3

Solubility(ies)

Solubility (water) 100 %

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity30 - 50 cP

Other information

Density8.61 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile69.5 - 70.5 %VOC< 180 g/l</th>

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** May be harmful if inhaled.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

#### Information on toxicological effects

Acute toxicity May be harmful if inhaled.

Product	Species	Test Results	
Pro Sanding Seal			
<u>Acute</u>			
Dermal			
LD50	Rabbit	46120 mg/kg	
Oral			
LD50	Rat	48380 mg/kg	
Components Species		Test Results	

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

Acute Dermal

LD50 Rabbit 9.5 g/kg

Components **Species Test Results** 

Oral

LD50 Rat 5.35 g/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

# 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	lest Results
Pro Sanding Seal			
Aquatic			
Crustacea	EC50	Daphnia	287938144, 48 hours estimated
Fish	LC50	Fish	40315.2773, 96 hours
Acute			
Crustacea	EC50	Daphnia	242625824, 48 hours estimated
Fish	LC50	Fish	20155.2617, 96 hours estimated

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of this product.

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not established.

**Toxic Substances Control Act (TSCA)** 

Annex II of MARPOL 73/78 and

the IBC Code

#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

or are designated

or are designated "inactive".

One or more components of the mixture are not on the TSCA 8(b) inventory

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Y

Yes

chemical

**Classified hazard** 

Acute toxicity (any route of exposure)

categories

SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

#### **US** state regulations

## California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### **International Inventories**

Country(s) or regionInventory nameOn inventory (yes/no)\*CanadaDomestic Substances List (DSL)NoCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 07-08-2016

 Revision date
 05-04-2023

Material name: Pro Sanding Seal sps us

Version # 04

HMIS® ratings Health: 1

Flammability: 0 Physical hazard: 0

**Disclaimer** No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is

responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Revision information Product and Company Identification: Alternate Trade Names

Physical & Chemical Properties: Multiple Properties Regulatory information: California Proposition 65