HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier PRO SEAL

Other means of identification

SDS number 583N-43A Product code HIL00747

Recommended useWood Floor SealRecommended restrictionsFor Labeled Use OnlyManufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

involving chemicals)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 2

Serious eye damage/eye irritation Category 2B

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear protective gloves.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Buyer assumes all risk and liability associated with disposal of this product (original concentration

or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry

container for recycling or reconditioning.

Hazard(s) not otherwise classified (HNOC)

None known.

Material name: PRO SEAL SDS US

HIL00747 Version #: 05 Revision date: 08-19-2021 Issue date: 03-18-2015

Supplemental information

NOTICE: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building.

NOTICE: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Dipropylene Glycol Methyl Ether		34590-94-8	1 - < 3
Propylene Glycol Butyl Ether		5131-66-8	1 - < 3
Other components below reports	ble levels		90 - 100

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delayed

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Move containers from fire area if you can do so without risk.

Fire fighting

Specific methods

equipment/instructions

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

Material name: PRO SEAL SDS US

7. Handling and storage

Precautions for safe handling Not available.

Conditions for safe storage, Store in tightly closed container. Store away from incompatible materials (see Section 10 of the including any incompatibilities SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US.	OSHA	Table Z-1	Limits for Air	Contaminants	(29 CFR	1910.1000)

Components	Туре	Value	
Dipropylene Glycol Methyl Ether (CAS 34590-94-8)	PEL	600 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Type	Value	
Dipropylene Glycol Methyl Ether (CAS 34590-94-8)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Components	Type	Value	
Dipropylene Glycol Methyl Ether (CAS 34590-94-8)	STEL	900 mg/m3	
		150 ppm	
	TWA	600 mg/m3	
		100 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Other Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory protectionNo personal respiratory protective equipment normally required. If engineering controls do not

maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved

respirator must be worn.

Thermal hazards None known.

Material name: PRO SEAL SDS US

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Milky, white emulsion

Physical state Liquid.
Form Liquid.
Color Milky white
Odor Mild solvent odor
Odor threshold Not available

PH 7 - 8

Melting point/freezing point Not applicable / Not available

Initial boiling point and boiling

range

> 200 °F (> 93.33 °C)

Flash point > 200.0 °F (> 93.3 °C) Tag Closed Cup

Evaporation rate < 1 Ethyl ether = 1
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%)Not available.Vapor pressure17.41 mm HgVapor density0.899 AIR=1Relative density1.038 at 77°F

Solubility(ies)

Solubility (water) 100 % Complete
Partition coefficient Not available

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available

Viscosity 10 - 30 cP Brookfield

Other information

Brookfield viscosity 10 - 30 cP

Density 8.64 lb/gal

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Percent volatile 70.5 - 71.5 %

VOC 129 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Material name: PRO SEAL SDS US

Eye contact Causes eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin

irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Not known.

Product Species Test Results

PRO SEAL

<u>Acute</u>

Dermal

LD50 Rabbit 600 g/kg

Oral

LD50 Rat 338 g/kg

Components Species Test Results

Dipropylene Glycol Methyl Ether (CAS 34590-94-8)

<u>Acute</u>

Dermal

LD50 Rabbit 9.5 g/kg

Oral

LD50 Rat 5.35 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Prolo

Prolonged inhalation may be harmful.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

PRO SEAL

Aquatic

Fish LC50 Fish 21457.1582 mg/l, 96 hours estimated

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Material name: PRO SEAL SDS US

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or

dilution) in violation of applicable law.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

One or more components of the mixture are not on the TSCA 8(b) inventory

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Toxic Substances Control Act (TSCA)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Skin corrosion or irritation

categories

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Material name: PRO SEAL SDS US Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information, including date of preparation or last revision

 Issue date
 03-18-2015

 Revision date
 08-19-2021

Version # 05

Further information This product meets Green Seal™ Standard GS-11 based on effective performance,

minimized/recycled packaging, and protective limits on VOCs and human toxicity. GreenSeal.org.

HMIS® ratings Health: 2

Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is

responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: PRO SEAL SDS US

HIL00747 Version #: 05 Revision date: 08-19-2021 Issue date: 03-18-2015

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).