

MATERIAL SAFETY DATA SHEET

IDENTITY (*As Used on Label and List*) Dust N Shine

Manufacturer's Name Wilen Manufacturing	Emergency Telephone Number 800-241-7371
Address 3760 Southside Ind. Pkwy	Telephone Number for Information 800-241-7371
Atlanta, GA 30354	Date Prepared 3/10/93

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
Mineral Seal Oil	5 MG/M3	5 MG/M3	64742-30-9	

SECTION III - Physical/Chemical Characteristics

Boiling Point	> 300 F	Specific Gravity (H₂O=1)	.8
Vapor Pressure (mm Hg)	< .01	Melting Point	
Vapor Density (AIR=1)	> AIR	Evaporation Rate (Butyl Acetate = 1)	< .01
Solubility in Water	NEGLIGIBLE		

Appearance and Odor Clear colorless liquid, mint odor.

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used) > 240 F	Flammable Limits	LEL	UEL
--	-------------------------	------------	------------

Extinguishing Media Regular Foam, CO2, Dry chemical

Special Fire Fighting Procedures
Wear self contained full-face breathing apparatus. Drums may build pressure and rupture under extreme heat.

Unusual Fire and Explosion Hazards
Concentrated vapors can be ignited by extreme heat or any ignition sources. Do not cut or weld drum.

Wilen Manufacturing believes that the information contained on this Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

SECTION V - Reactivity Data

Stability	Unstable	Conditions to Avoid	Extreme temperatures.
	Stable XX		

Incompatibility (Materials to Avoid) Strong acids and oxidizers.

Hazardous Decomposition or Byproducts CO, CO2

Hazardous Polymerization	May Occur	Conditions to Avoid	None.
	Will Not Occur XX		

SECTION VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
--------------------	-------------	-------	------------

Health Hazards (Acute and Chronic) Overexposure and toxicity depend upon duration of exposure. Symptoms of overexposure include dizziness, nausea, headache and even loss of consciousness.

Carcinogenicity:	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
------------------	---------	---------------------	--------------------

Signs and Symptoms of Exposure

Medical Conditions Generally Aggravated by Exposure

Emergency and First Aid Procedures Inhalation: Remove to fresh air. If breathing has stopped, administer artificial respiration. Call a physician. Ingestion: Do not induce vomiting. Contact a physician immediately. Eye Contact: Flush eyes immediately with water for at least 15 min. Call a physician. Skin Contact: Flush with plenty of water while removing contaminated clothing and shoes. Wash with plenty of soap and water for 15 minutes.

SECTION VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Eliminate all ignition sources. Contain spill and pump to recover. Small spills may be mopped up. Flush area with water.

Waste Disposal Method Dispose of in accordance with all Federal, State, and local regulations.

Precautions to Be Taken in Handling and Storage Store in cool place away from all ignition sources. Keep container closed when not in use.

Other Precautions

SECTION VIII - Control Measures

Respiratory Protection (Specify Type) None required with adequate venting.

Ventilation Equivalent to outdoors.	Local Exhaust	Special
	Mechanical (General)	Other
Protective Gloves	Recommended	Eye Protection Recommended

Other Protective Clothing or Equipment Explosion proof motor for mechanical venting.

Work/Hygiene Practices Wash hands thoroughly after use.