

# SAFETY DATA SHEET

# TROJ185AES

### 1. Identification

Product identifier	Lead Acid Battery
Other means of identification	
Synonyms	Wet Acid Storage Battery
Recommended use	Storage battery.
<b>Recommended restrictions</b>	None known.
Manufacturer/Importer/Supplie	r/Distributor information
Company name	Trojan Battery Company, LLC
Address	12380 Clark Street
	Santa Fe Springs, CA 90670
	United States of America
Website	www.trojanbattery.com
Telephone	+1(562) 236-3000 or +1(800) 423-6569
EHS Technical contact	+1(978) 727-2206 or +1(610) 858-6192
Emergency telephone	CHEMTREC: (800) 424-9300 (US & CA)
	International: +1(703) 527-3887

### 2. Hazard(s) identification

Physical hazards	Corrosive to metals	Category 1
Health hazards	Skin corrosion/irritation	Category 1A
	Serious eye damage/eye irritation	Category 1
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 1A
	Reproductive toxicity	Effects on or via lactation
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure	Category 1 (blood, central nervous system, kidneys)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
OSHA defined hazards	Not classified.	

### Label elements

Signal word Hazard statement

The materials contained in this product may only represent a hazard if the integrity of the cell or battery is compromised. Listed below are the hazards anticipated when the battery is physically, thermally, or electrically abused:

May be corrosive to metals. Causes severe skin burns and eye damage. May cause cancer. May damage fertility or the unborn child. May cause harm to breast-fed children. May cause respiratory irritation. Causes damage to organs (blood, central nervous system, kidneys) through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.

Danger

Precautionary statement	
Prevention	Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Absorb spillage to prevent material damage. Collect spillage.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Under normal conditions of processing and use, exposure to the chemical constituents in this product is unlikely. Batteries may get hot, explode or ignite and cause serious injury if mishandled, crushed or abused. When exposed to heat, when short circuited, or when exposed to incompatible materials, the battery may rupture and release hazardous substances. These substances can explode and burn. Burning batteries may emit toxic fumes.

## 3. Composition/information on ingredients

### **Mixtures**

Chemical name	CAS number	%
Lead	7439-92-1	62
Sulfuric acid	7664-93-9	31
Antimony	7440-36-0	1
Tin	7440-31-5	0.2
Arsenic	7440-38-2	0.1

### **Case and Separators**

Chemical name	Common name and synonyms	CAS number	%
Polypropylene		9003-07-0	3.5
Silica		112926-00-8	1.2
Natural rubber		9006-04-6	0.5
Oil		64742-52-5	0.5
Composition comments	The ingredients listed in section 3 are contain occurs if battery is mechanically, thermally or All concentrations are in percent by weight.		of exposure only

Composition	comments
-------------	----------

	All concentrations are in percent by weight.
4. First-aid measures	
Inhalation	Exposure to contents of an open or damaged battery: Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention immediately.
Skin contact	Exposure to contents of an open or damaged battery: Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Exposure to contents of an open or damaged battery: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Exposure to contents of an open or damaged battery: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed	Under normal conditions of intended use, this product is not expected to be a health risk. Exposure to contents of an open or damaged battery: Narcosis. Behavioral changes. Decrease in motor functions. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Foam. Special powder against metal fires. Dry sand.
Unsuitable extinguishing media	Leak from a damaged or opened battery: Do not use water unless flooding amounts are available. Do not use carbon dioxide directly on cells.
Specific hazards arising from the chemical	In the event of fire and/or explosion do not breathe fumes. During fire, hazardous combustion products are released that may include: Carbon oxides. Sulfur oxides. Fumes of metal oxides. Hydrogen and oxygen gases are produced in the cells during normal battery operation (hydrogen is flammable and oxygen supports combustion). These gases enter the air through the vent caps. To avoid the chance of fire or explosion, keep sparks and other sources of ignition away from battery.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire fighting equipment/instructions	Fight fire from protected location or safe distance. Keep upwind. Move containers from fire area if you can do so without risk. Avoid discharge into drains, water courses or onto the ground.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Under normal use, the battery does not exhibit flammable properties. In the event that the battery is abused and disassembly of the battery occurs resulting in exposure of internal components, the exposed solution may be flammable and/or corrosive. Exposure to excessive heat may lead to venting or rupture of the sealed battery, exposing the internal components which may be corrosive and/or flammable. Vented gas would be flammable when in sufficient concentration.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. In the event of damage resulting in a leak or exposed materials, avoid contact with contents of an open or damaged cell or battery. Wear protective clothing as described in Section 8 of this safety data sheet.
Methods and materials for containment and cleaning up	Leak from a damaged or opened battery: Contain spillage with sand or earth. Place in a designated labeled waste container, dispose as hazardous waste. For waste disposal, see Section 13 of the SDS.
Environmental precautions	Avoid allowing material from exposed battery to contaminate soil, sanitary sewers, or waterways.
7. Handling and storage	

**Precautions for safe handling** Do not allow conductive material to touch the battery terminals. A dangerous short-circuit may occur and cause battery failure and fire. Protect against physical damage. Do not open, disassemble, crush or burn battery. Do not expose battery to extreme heat or fire. Elevated temperatures can result in reduced battery service life. Wash hands thoroughly after handling. Do not release into the environment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities** Store locked up. Keep out of reach of children. Prevent short circuits. Store in original packaging. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep at room temperature. Avoid contact with water and moisture. Protect from heat and direct sunlight. Inspect periodically for damage or leaks. Store away from incompatible materials (See Section 10).

### 8. Exposure controls/personal protection

### **Occupational exposure limits**

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)<br/>TypeValueComponentsTypeValueArsenic (CAS 7440-38-2)TWA0.01 mg/m3Lead (CAS 7439-92-1)TWA0.05 mg/m3

Lead Acid Battery

US. OSHA Table Z-1 Limit Components		Туре	-		Value	
Antimony (CAS 7440-36-0)		PEL			0.5 mg/m3	
Sulfuric acid (CAS 7664-93-9)		PEL			1 mg/m3	
Case and Separators		Туре			Value	Form
Oil (CAS 64742-52-5)		PEL			5 mg/m3	Mist.
					2000 mg/m3	
					500 ppm	
US. OSHA Table Z-3 (29 C Case and Separators	FR 1910.1000)	) Туре			Value	Form
Silica (CAS 112926-00-8)		TWA			5 mg/m3	Respirable fraction.
					15 mg/m3	Total dust.
					0.8 mg/m3	
					20 mppcf	
US. ACGIH Threshold Lim	it Values					
Components		Туре			Value	Form
Antimony (CAS 7440-36-0)		TWA			0.5 mg/m3	
Arsenic (CAS 7440-38-2)		TWA			0.01 mg/m3	
Lead (CAS 7439-92-1)		TWA			0.05 mg/m3	
Sulfuric acid (CAS 7664-93-9)		TWA			0.2 mg/m3	Thoracic fraction.
Case and Separators		Туре			Value	Form
Natural rubber (CAS 9006-04-6)		TWA			0.0001 mg/m3	Inhalable fraction.
Oil (CAS 64742-52-5)		TWA			5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide Components	to Chemical H	lazards Type			Value	
Antimony (CAS 7440-36-0)		TWA			0.5 mg/m3	
Arsenic (CAS 7440-38-2)		Ceilin	g		0.002 mg/m3	
Lead (CAS 7439-92-1)		TWA			0.05 mg/m3	
Sulfuric acid (CAS 7664-93-9)		TWA			1 mg/m3	
Case and Separators		Туре			Value	
Silica (CAS 112926-00-8)		TWA			6 mg/m3	
ogical limit values						
ACGIH Biological Exposu Components	re Indices Value		Determinant	Specimen	Sampling 1	Гіme
Arsenic (CAS 7440-38-2)	35 µg/l		Inorganic arsenic, plus methylated metabolites, as As	Urine	*	
Lead (CAS 7439-92-1)	200 µg/l		Lead	Blood	*	
* - For sampling details, plea	ase see the so	urce docu	ment.			
osure guidelines	intended p	urpose.		tances are no	ot expected when	product is used for its
US ACGIH Threshold Limi		n designa <sup>.</sup>	tion			
Natural rubber (CAS 90	06-04-6)		Danger	of cutaneous	s absorption	

### US. NIOSH: Pocket Guide to Chemical Hazards

Arsenic (CAS 7440-38-2)	Can be absorbed through the skin.
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Leak from a damaged or opened battery: Use approved safety goggles or face shield.
Skin protection	
Hand protection	Leak from a damaged or opened battery: Wear chemical-resistant, impervious gloves. Full contact: Glove material: Nitrile. Use gloves with breakthrough time of 30 minutes. Minimum glove thickness 12 mil. Incidental contact: Glove material: Nitrile. Use gloves with breakthrough time of 10 minutes. Minimum glove thickness 5 mil. Other suitable gloves can be recommended by the glove supplier.
Other	None under normal conditions. Leak from a damaged or opened battery: Wear suitable coveralls to prevent exposure to the skin.
Respiratory protection	None under normal conditions. Leak from a damaged or opened battery: In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	No protection is ordinarily required under normal conditions of use.
General hygiene considerations	Do not store food, drink and tobacco near the product. Wash hands after handling. Practice good housekeeping. Observe good industrial hygiene practices.

# 9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Battery.
Color	No data available.
Odor	Odorless. If leaking: sharp, penetrating, pungent odor for internal components.
Odor threshold	Not applicable unless individual components exposed.
рН	1 - 2 (Sulfuric acid/battery electrolyte)
Melting point/freezing point	Not applicable unless individual components exposed.
Initial boiling point and boiling range	410 - 473 °F (210 - 245 °C) (Sulfuric acid/battery electrolyte)
Flash point	Not applicable unless individual components exposed.
Evaporation rate	< 1 (n-Butyl acetate=1) (Sulfuric acid/battery electrolyte)
Flammability (solid, gas)	Contains one or more components that will burn if involved in a fire.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not applicable unless individual components exposed.
Explosive limit - upper (%)	Not applicable unless individual components exposed.
Vapor pressure	10 mmHg (Sulfuric acid/battery electrolyte)
Vapor density	> 1 (Air=1) (Sulfuric acid/battery electrolyte)
Relative density	1.215 - 1.35 (Water=1) (Sulfuric acid/battery electrolyte)
Solubility(ies)	
Solubility (water)	100 % (Sulfuric acid/battery electrolyte)
Partition coefficient (n-octanol/water)	Not applicable unless individual components exposed.
Auto-ignition temperature	Not applicable unless individual components exposed.
Decomposition temperature	Not applicable unless individual components exposed.
Viscosity	Not applicable unless individual components exposed.
Other information	
Density	1.215 - 1.35 g/cm <sup>3</sup> (Sulfuric acid/battery electrolyte)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

## 10. Stability and reactivity

Reactivity	Exposure to contents of an open or damaged battery: May be corrosive to metals. Reacts with water with release of heat.
Chemical stability	Product is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Exposure to contents of an open or damaged battery: Contact with metals may evolve flammable hydrogen gas.
Conditions to avoid	Heat, sparks, flames, elevated temperatures. Protect against direct sunlight. Water, moisture. Shocks and physical damage. Do not open, disassemble, crush or burn battery. Do not allow conductive material to touch the battery terminals. A dangerous short-circuit may occur and cause battery failure and fire.
Incompatible materials	Strong oxidizing agents. Strong reducing agents. Combustibles. Organic material. Metals. Water. Bases. Halides. Halogenated compounds. Potassium nitrate. Permanganates. Peroxides. Bromine azide.
Hazardous decomposition products	Irritating and/or toxic fumes and gases may be emitted upon the products decomposition. Sulfur trioxide. Carbon oxides. Sulfuric acid mist. Sulfur dioxide. Hydrogen sulfide. Arsine gas. Fumes of metal oxides.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Under normal conditions of intended use, this material is not expected to be an inhalation hazard. Exposure to contents of an open or damaged battery: May cause respiratory irritation.
Skin contact	Under normal conditions of intended use, this material does not pose a skin hazard. Exposure to contents of an open or damaged battery: Causes skin burns.
Eye contact	Under normal conditions of intended use, this material does not pose an eye hazard. Exposure to contents of an open or damaged battery: Causes serious eye damage.
Ingestion	Under normal conditions of intended use, this material does not pose a risk to health. Exposure to contents of an open or damaged battery: May have a corrosive effect on the digestive canal.
Symptoms related to the physical, chemical and toxicological characteristics	Under normal conditions of intended use, this product is not expected to be a health risk. Exposure to contents of an open or damaged battery: Narcosis. Behavioral changes. Decrease in motor functions. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects. May cause respiratory irritation. Coughing.

### Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.	
Components	Species	Test Results
Arsenic (CAS 7440-38-2)		
Acute		
Oral		
LD50	Mouse	145 mg/kg
	Rat	763 mg/kg
Sulfuric acid (CAS 7664-93-9	9)	
Acute		
Oral		
LD50	Rat	2140 mg/kg
Case and Separators	Species	Test Results
Oil (CAS 64742-52-5)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
Aerosol		
LC50	Rat	> 5.53 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Case and Separators	Species	Test Results	
Silica (CAS 112926-00-8)			
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 2200 mg/m³, 4 hours	
Oral			
LD50	Rat	> 5000 mg/kg	
Skin corrosion/irritation	Exposure to contents of an or	pen or damaged battery: Causes skin burns.	
Serious eye damage/eye	•	pen or damaged battery: Causes skin burns.	
rritation	Exposure to contents of an of	pen of damaged ballery. Causes senous eye damage.	
Respiratory or skin sensitization			
ACGIH sensitization			
	halable allergenic proteins	Dermal sensitization	
(0.10 0000 0.10)		Respiratory sensitization	
Respiratory sensitization	Not classified.		
Skin sensitization	Not classified.		
Serm cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are		
	mutagenic or genotoxic.		
Carcinogenicity	Exposure to contents of an open or damaged battery: May cause cancer.		
IARC Monographs. Overall E	Evaluation of Carcinogenicity	,	
Arsenic (CAS 7440-38-2)		1 Carcinogenic to humans.	
Lead (CAS 7439-92-1)		2B Possibly carcinogenic to humans.	
Oil (CAS 64742-52-5)		3 Not classifiable as to carcinogenicity to humans.	
Polypropylene (CAS 9003 Silica (CAS 112926-00-8)		3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.	
NTP Report on Carcinogens		S Not classifiable as to cardinogenicity to numaris.	
Arsenic (CAS 7440-38-2)		Known To Be Human Carcinogen.	
Lead (CAS 7439-92-1)		Reasonably Anticipated to be a Human Carcinogen.	
OSHA Specifically Regulate	d Substances (29 CFR 1910.1	001-1053)	
Arsenic (CAS 7440-38-2)		Cancer	
Reproductive toxicity	Exposure to contents of an open or damaged battery: May damage fertility or the unborn child May cause harm to breastfed babies.		
Specific target organ toxicity - single exposure	Exposure to contents of an open or damaged battery: May cause respiratory irritation.		
Specific target organ toxicity - epeated exposure	Exposure to contents of an open or damaged battery: Causes damage to organs (blood, central nervous system, kidneys) through prolonged or repeated exposure.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Exposure to contents of an or	pen or damaged battery: Causes damage to organs through	
	prolonged or repeated exposure. Lead may produce maternal toxicity, toxicity to the fetus, and adverse effects to blood, bone marrow, central/peripheral nervous systems, kidney, liver, and reproductive system. Prolonged exposure may cause chronic effects.		
Further information	Exposure to hazardous ingredients is not anticipated under normal conditions of use.		
2. Ecological information			
Ecotoxicity		ed under normal use conditions.	
		only anticipated when the integrity of a battery casing is	
	compromised:		
	Very toxic to aquatic life with	long lasting effects.	

Components		Species	Test Results	
Sulfuric acid (CAS 7664-93-9	9)			
Aquatic				
Acute				
Crustacea	EC50	Daphnia magna	29 mg/l, 24 Hours	
Fish	LC50	Lepomis macrochirus	> 16 - < 28 mg/l, 96 Hours	
Chronic				
Crustacea	NOEC	Invertebrates (Invertebrates)	0.15 mg/l	
Fish	NOEC	Brook trout (Salvelinus fontinalis)	0.13 mg/l	
Persistence and degradability	The produ	uct contains inorganic compounds which are	e not biodegradable.	
Bioaccumulative potential	The produ	act contains potentially bioaccumulating sub	stances.	
Partition coefficient n-octa Sulfuric acid (CAS 7664-93-9		log Kow) -2.2		
Mobility in soil	The produ	The product is not mobile in soil. Some components from a leaking battery may be mobile.		
Other adverse effects		This product contains one or more substances identified as hazardous air pollutants (HAPs) per the US Federal Clean Air Act (see section 15).		
13. Disposal consideratio	ons			
Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	D008: Wa D004: Wa The waste	D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel] D008: Waste Lead D004: Waste Arsenic The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	product re	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging		Since emptied containers may retain product residue, follow label warnings even after container emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.		
14. Transport information	า			
DOT				

DOT	
UN number	UN2794
UN proper shipping name	Batteries, wet, filled with acid, electric storage
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	-
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	159
Packaging non bulk	159
Packaging bulk	159
ΙΑΤΑ	
UN number	UN2794
UN proper shipping name	Batteries, wet, filled with acid electric storage
Transport hazard class(es)	
Class	8
Subsidiary risk	
Packing group	-
Environmental hazards	Yes

ERG Code 8L structions, SDS and emergency procedures before bandling d a state in

Special precautions for use IMDG	r Read safety	Read safety instructions, SDS and emergency procedures before handling.				
UN number	UN2794	11N12704				
UN proper shipping name		BATTERIES, WET, FILLED WITH ACID electric storage				
Transport hazard class(es)	2,11121121	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		lorago		
Class	8					
Subsidiary risk	-					
Packing group	-					
Environmental hazards						
Marine pollutant	Yes					
EmS	F-A, S-B					
-	Read safety instructions, SDS and emergency procedures before handling.					
Transport in bulk according to		Not applicable.			9.	
Annex II of MARPOL 73/78 and						
the IBC Code						
15 Degulatory informatio						
15. Regulatory informatio US federal regulations		t is a "Hazardou	is Chemical" as defined	d by the OSHA Hazard	Communication	
03 lederal regulations		9 CFR 1910.12			Communication	
TSCA Section 12(b) Ex	oort Notificati	ion (40 CFR 70	7, Subpt. D)			
Lead (CAS 7439-92	·1)		0.1 % Annual Expo	ort Notification required		
CERCLA Hazardous Su	bstance List	(40 CFR 302.4)	1			
Antimony (CAS 744	0-36-0)		Listed.			
Arsenic (CAS 7440-	,		Listed.	Listed.		
	Lead (CAS 7439-92-1)		Listed.			
Sulfuric acid (CAS 7			Listed.			
SARA 304 Emergency I	elease notific	cation				
Sulfuric acid (CAS 7	,		1000 LBS			
OSHA Specifically Reg	ulated Substa	ances (29 CFR	1910.1001-1053)			
Arsenic (CAS 7440-	38-2)		Cancer			
Lead (CAS 7439-92-1)		Reproductive toxicity				
Arsenic (CAS 7440-38-2)		Liver				
	Lead (CAS 7439-92-1)		Central nervous system			
Arsenic (CAS 7440-38-2)		Skin				
Lead (CAS 7439-92-1) Arsenic (CAS 7440-38-2)		Kidney Respiratory irritation				
			Blood			
			Nervous system			
		Acute toxicity				
Arsenic (CAS 7440-			Acute toxicity			
Toxic Substances Control	Act (TSCA)		components are either l ignated "active" or exer	listed on the TSCA 8(b)	inventory and	
Superfund Amendments and Re	authorization		-			
SARA 302 Extremely hazar						
Chemical name CA	S number	Reportable	Threshold	Threshold	Threshold	
		quantity	planning quantity	planning quantity,	planning quantity,	
		(pounds)	(pounds)	lower value	upper value	
				(pounds)	(pounds)	
	64-93-9	1000	1000			
SARA 311/312 Hazardous chemical	Yes					
Classified hazard	Corrosive to					
categories		on or irritation				

Lead Acid Battery

Chemical name Antimony Arsenic Lead Sulfuric acid ther federal regulations Clean Air Act (CAA) Section 112 Hazardous Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2) Lead (CAS 7439-92-1)		% by wt. 1 0.1 62 31
Arsenic Lead Sulfuric acid ther federal regulations Clean Air Act (CAA) Section 112 Hazardous Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2)	7439-92-1 7664-93-9 s Air Pollutants (HAPs) List	62
Sulfuric acid her federal regulations Clean Air Act (CAA) Section 112 Hazardous Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2)	7664-93-9 s Air Pollutants (HAPs) List	-
her federal regulations Clean Air Act (CAA) Section 112 Hazardous Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2)	s Air Pollutants (HAPs) List	31
Clean Air Act (CAA) Section 112 Hazardous Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2)		
Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2)		
Arsenic (CAS 7440-38-2)	tal Release Prevention (40 CF	
	tal Release Prevention (40 CI	
Clean Air Act (CAA) Section 112(r) Acciden		FR 68.130)
Sulfuric acid (CAS 7664-93-9)		
Safe Drinking Water Act Contains comp (SDWA)	ponent(s) regulated under the S	afe Drinking Water Act.
Drug Enforcement Administration (DE Chemical Code Number	A). List 2, Essential Chemical	s (21 CFR 1310.02(b) and 1310.04(f)(2) and
Sulfuric acid (CAS 7664-93-9)	6552	
Drug Enforcement Administration (DE		al Mixtures (21 CFR 1310.12(c))
Sulfuric acid (CAS 7664-93-9)	20 %WV	
DEA Exempt Chemical Mixtures Code		
Sulfuric acid (CAS 7664-93-9)	6552	
state regulations		
US. Massachusetts RTK - Substance List		
Antimony (CAS 7440-36-0)		
Arsenic (CAS 7440-38-2)		
Lead (CAS 7439-92-1)		
Silica (CAS 112926-00-8)		
Sulfuric acid (CAS 7664-93-9)		
US. New Jersey Worker and Community Ri	ght-to-Know Act	
Antimony (CAS 7440-36-0)		
Arsenic (CAS 7440-38-2)		
Lead (CAS 7439-92-1)		
Silica (CAS 112926-00-8)		
Sulfuric acid (CAS 7664-93-9)		
US. Pennsylvania Worker and Community	Right-to-Know Law	
Antimony (CAS 7440-36-0)		
Arsenic (CAS 7440-38-2)		
Lead (CAS 7439-92-1)		
Sulfuric acid (CAS 7664-93-9)		
US. Rhode Island RTK		
Antimony (CAS 7440-36-0)		
Arsenic (CAS 7440-38-2)		
Lead (CAS 7439-92-1)		
Oil (CAS 64742-52-5)		
Silica (CAS 112926-00-8)		
Sulfuric acid (CAS 7664-93-9)		
California Proposition 65		
	d birth defects or other reprodu	g Lead, which is known to the State of California ctive harm. For more information go
California Proposition 65 - CRT: Listed		
-	-	
Arsenic (CAS 7440-38-2)	Listed: Februa	-
Lead (CAS 7439-92-1) Sulfuric acid (CAS 7664-93-9)	Listed: Octobe Listed: March	
California Proposition 65 - CRT: Listed		14, 2000
-	=	
Lead (CAS 7439-92-1)	Listed: Februa	
California Proposition 65 - CRT: Listed	-	
Lead (CAS 7439-92-1)	Listed: Februa	ary 27, 1987
ead Acid Battery		

### California Proposition 65 - CRT: Listed date/Male reproductive toxin

Lead (CAS 7439-92-1) Listed: February 27, 1987 US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Antimony (CAS 7440-36-0) Arsenic (CAS 7440-38-2) Lead (CAS 7439-92-1) Oil (CAS 64742-52-5) Sulfuric acid (CAS 7664-93-9)

### International Inventories

Country(s) or region	Inventory name Or	n inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	13-June-2022
Revision date	-
Version #	01
NFPA ratings	3 0

Disclaimer

Trojan Battery Company, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.