

# Protective Coating

HILLYARD  
FLOOR CARE

A water emulsion finish formulated to protect synthetic sports floors, enhance their appearance, and make them easier to clean and maintain. Protective Coating stands up to scuffing, scratching, rubber burns, and heel marks. And Protective Coating retains its gloss even after months of wear in the busiest of gyms. It not only helps protect the floor, but makes cleaning, dust mopping, and periodic damp mopping much easier. Rubber burns, scuffs, and dirt are held in the surface of the film where they can be easily removed.

## Features & Benefits

- 18% solids clear acrylic copolymer for enhanced appearance.
- Self-leveling for easy application.
- Minimum maintenance required.

## Directions

**DIRECTIONS:** Always check with the flooring manufacturers warranty concerning the use of maintenance products on your floor. Once warranty has expired, or at your discretion, you decide to use Protective Coating, follow the steps below.

**PREPARATION: New Floors (Not Opened to Traffic):** Allow the moisture cured urethane coating to cure at least two weeks, then scrub the floor with a medium scrub pad on a smooth floor or scrub brush on mild textured floor. Use solution of Hillyard Salvation with automatic scrubbing machine or single brush floor machine. Vacuum and rinse thoroughly with clean water. Allow the floor to dry thoroughly, at least one hour.

**Old Floors (and New Floors Soiled by Traffic):** Scrub the floor thoroughly with a solution of Hillyard Salvation using a stripping pad on smooth floor or scrubbing brush on mild textured floor. Vacuum and rinse thoroughly with clean water. Allow the floor to dry at least one hour.

**APPLICATION:** Apply a moderate, uniform coat of Hillyard Protective Coating with a clean synthetic mop and allow to dry at least one hour. Apply an additional thin coat or two depending on floor porosity, allowing one hour between coats.

**NOTICE:** Proper curing between coats prevents pulling or streaking. Humidity and temperature conditions affect curing time.

**MAINTENANCE:** Dust mop as required to remove loose soil and grit with Hillyard Super Hil-Tone treated dust mop. Damp mop or auto scrub when necessary using Hillyard Clean Scrub.

**IMPORTANT:** Do not use an ammoniated cleaner for daily care.

**NOTICE:** Keep container closed when not in use. Do not pour unused coating back into container. Best results are obtained with adequate ventilation and floor temperatures above 60°F (16°C).



## Safety

See material safety data sheet and product label for safety information, handling and proper use.

### HMIS

#### Concentrate

Health	0
Flammability	0
Reactivity	0

## Technical Specifications

Color	White
Scent	Mild Ammonia
Appearance	Milky Emulsion
pH (concentrate)	7.75 - 8.75
Non-Volatile Matter	17.50 - 18.50%
Dilution Rate	RTU

## Availability

Item	Pack
HIL0029106	4 - 1 Gallon Containers
HIL0029107	1 - 5 Gallon Bag-In-Box

HILLYARD

P.O. Box 909  
St. Joseph, MO 64502  
1-800-365-1555  
www.hillyard.com