

HV-Pro

HILLYARD
I-FORCE®

An industrial vehicle wash specifically formulated for hand vehicle washing systems. HV-Pro removes most exhaust deposits, road film, and bug residue from painted vehicle surfaces, cleans aluminum siding, painted wood, and painted metal surfaces. HV-Pro rinses residue-free and water will bead up for that "just waxed look". For use with hot or cold water, HV-Pro is heat stable to 180° Fahrenheit, and contains no solvents, free acids or phosphates.

Features & Benefits

- Great foaming characteristics.
- Effective in hot or cold water.
- Can also be used in pressure washers.

Directions

Dilute product according to label directions. Allow solution to penetrate soil for 5 minutes. Rinse thoroughly with clean water. Can use with brush cleaning.

Light cleaning: Dilute 1oz. HV-Pro into 1 gallon of water.

Medium Cleaning: Dilute 3oz. HV-Pro into 1 gallon of water.

Heavy Cleaning: Dilute 6oz. HV-Pro into 1 gallon of water.

NOTICE: Test solution on inconspicuous area when using on a surface for first time. DO NOT PROCEED if adverse effects occur on paint, metal, or other vehicle surfaces.

HV-Pro can also be used through a pressure washer, however if excessive foam occurs, use a lighter dilution of HV-Pro or use Hillyard CV-Pro in its place.



Safety

See material safety data sheet and product label for safety information, handling and proper use.

HMIS

Concentrate

Health	2
Flammability	0
Reactivity	0

Technical Specifications

Color	Green
Scent	Non-Objectionable
Appearance	Clear, green liquid
pH (concentrate)	8.00 - 9.50
Non-Volatile Matter	6.75 - 7.75%
Dilution Rate	1:20 - 1:128

Availability

Item	Pack
HIL0045306	4 - 1 Gallon Containers
HIL0045309	1 - 55 Gallon Drum

HILLYARD



P.O. Box 909
St. Joseph, MO 64502
1-800-365-1555
www.hillyard.com