HTG Concrete Seal

HTG(gray) Concrete Seal is a 2-part, high-solid epoxy resin formulation for extreme durability that dries gray. Use HTG to transform bare concrete or previously coated concrete floors into showroom caliber floors that deliver the ultimate in protection and appearance. For ultimate results, apply a complete 4 level system consisting of Hillyard Concrete Primer, HTG Concrete Seal, Decorative Flakes, and HT Clear Concrete Seal. Or, apply HTG Gray as a single coat over Hillyard Concrete Primer.

DEFENSE[®]



Features & Benefits

- Extreme duty, 2-part, high solids epoxy resin.
- Great hot tire resistance.
- Designed for indoor use, low odor, 12 hour dry time.

Directions

See Attached

Traffic







Forklift

Power Dollies

s Carts

Pedestrian

ACIDIC

Resistance



Good



WATER



SOLVENT

E.



ALKALINE

Certifications, Registrations & Notes

Meets slip resistance using ASTM D2047 and Underwriters Laboratories, Inc's, Method 410.

HILLYARD

Safety

See material safety data sheet and product label for safety information, handling and proper use.

HMIS	Concentrate
Health	3
Flammability	0
Reactivity	0

Technical Specifications

Color	Gray
Scent	Mild
Appearance	Emulsion
pH (concentrate)	7.00 - 9.00
Non-Volatile Matter	57.00 - 62.00%
Dilution Rate	RTU

Availability

ltem	Pack
HIL0050006	1 - 1 Gallon Kit
HIL0050007	1 - 5 Gallon Kit

Coverage Rate

Approx. coverage: 300 - 400 sq. ft./gallon

P.O. Box 909 St. Joseph, MO 64502 1-800-365-1555 www.hillvard.com