

A technologically advanced, optimum-solids polish perfected for high speed and ultra-high speed floor care. It is based on high-tech polymers that will deliver durable, deep gloss protection for your floors. Endeavour was designed to be the polish of choice for areas where heavy traffic, grit, dirt, scuffs, and black heel marks torture an ordinary polish to a dull death. It stands up to repeated cleaning with detergents and keeps shining.

## Features & Benefits

- Stands up to repeat cleaning with detergents and keeps shining.
- Repeated burnishing just makes it better.
- Levels beautifully and dries fast for building a durable base.

## Directions

**PREPARATION:** Strip other finishes from the floor with HILLYARD ASSAULT or DEVASTATOR following label directions. Use autoscrubber or floor machine with black pad or brush (do not use abrasive pads on tile containing asbestos). Remove stripping solution with autoscrubber or wet vacuum. Heavy rinse with HILLYARD NUTRA-RINSE and pick up with autoscrubber or wet vacuum. Damp mop all flooring twice with clean, cool water. Allow the floor to dry.

**APPLICATION:** When using a sealer, apply a minimum of 5 coats of ENDEAVOUR with a clean synthetic mop. Allow each coat to dry a minimum of 30 minutes before applying the next. When a sealer is not used, apply a minimum of 7 coats of ENDEAVOUR.

**NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C).

**FLOOR PAD RECOMMENDATIONS:** **Strip** - black; **Scrub and Recoat** - blue or green; **Autoscrubbing** - HILLYARD UHS Cleaner Pad, 3M 5000 TopLine Pre-Burnish, or 3M 5100 Red; **Burnishing** - HILLYARD 100-D Polythermal or HILLYARD Beige Polythermal.

**NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is very porous, seal with HILLYARD HIL-TEX+, SEAL 340 or SEAL 341 before applying ENDEAVOUR. If stains are a problem, seal with STRONG GUARD.

**NOTE:** Do not pour unused finish or seal back into the original container.

**High Speed Burnishing:** Because high speed burnishing is affected by many variables, including equipment type, pad pressure, frequency of burnishing, and traffic loads contact Hillyard Technical Service for pad recommendations.

## Certifications, Registrations & Notes

Classified by Underwriters Laboratories, Inc.® as to slip resistance. (1865).



## Safety

See material safety data sheet and product label for safety information, handling and proper use.

### HMIS

	Concentrate
Health	1
Flammability	0
Reactivity	0

## Technical Specifications

Color	White
Scent	Non-Objectionable
Appearance	Milky Emulsion
pH (concentrate)	8.00 - 9.00
Non-Volatile Matter	18.00%
Dilution Rate	RTU

## Availability

Item	Pack
HIL0052506	4 - 1 Gallon Containers
HIL0052507	1 - 5 Gallon Bag-In-Box
HIL0052509	1 - 55 Gallon Drum

**Coverage Rates:** 1,500 - 2,000 Sq. Ft. per Gallon  
*Rates can vary greatly based on surface and application method.*