# **One Plus®**

Green Seal certified. A new-generation floor polish that's formulated to be durable, easy to use, and deliver a deep gloss. One Plus will give your floors a tough and durable shine that will stand up to scuffing, scratching, and black heel marks... even in critical high traffic areas. One Plus contains no heavy metals (a potential issue for sewage treatments facilities). One Plus is a natural choice for maintaining both resilient and hard surface floors in schools, offices, hospitals, malls...and a multitude of other facilities.

### **Features & Benefits**

- Durable, easy to use, and delivers a deep gloss.
- Contains no heavy metals.
- Can apply multiple coats in one day to save time and labor.

## Directions

**PREPARATION:** Strip other polishes from the floor with HILLYARD GREEN SELECT STRIPPER, SUPER STRIP or DEVASTATOR. (Do not use abrasive pads on tile containing asbestos.) Remove the stripping solution with a wet vac. Rinse with HILLYARD NUTRA-RINSE solution and pick up with a wet vac or autoscrubber. Damp mop twice. Allow floor to dry.

**APPLICATION:** Using a clean synthetic mop, apply 3 coats of ONE PLUS allowing a minimum of 30 minutes between coats. Additional coats of ONE PLUS may be applied, provided adequate dry time (at least one hour) is allowed between coats. Temperature, humidity, and air movement affect curing time.

**NOTICE:** ONE PLUS can be used as its own seal even on porous floors. Proper drying between coats prevents pulling or streaking with any polish. For best results, allow 30 minutes drying time between coats.

**NOTE:** Do not pour unused polish back into container. Best results are obtained with adequate ventilation and floor temperatures above 60°F (16°C).

**High Speed Burnishing:** Because high speed burnishing is affected by many variables, including equipment type, pad pressure, frequency of burnishing, and traffic loads contact Hillyard Technical Service for pad recommendations.

# **Certifications, Registrations & Notes**

**Green Seal Certified** 

\*This product meets Green Seal<sup>™</sup> Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

Classified by Underwriters Laboratories, Inc.® as to slip resistance. (186S).

# FLOOR CARE



### Safety

See material safety data sheet and product label for safety information, handling and proper use.

HMIS	Concentrate
Health	1
Flammability	0
Reactivity	0

### **Technical Specifications**

Color	White
Scent	Non-Objectionable
Appearance	Milky Emulsion
pH (concentrate)	7.00 - 8.00
Non-Volatile Matter	18.00%
Dilution Rate	RTU

### **Availability**

ltem	Pack
HIL0052706	4 - 1 Gallon Containers
HIL0052707	1 - 5 Gallon Bag-In-Box
HIL0052709	1 - 55 Gallon Drum

**Coverage Rates:** 1,500 - 2,000 Sq. Ft. per Gallon *Rates can very greatly based on surface and application method.* 

P.O. Box 909 St. Joseph, MO 64502 1-800-365-1555 www.hillyard.com