

HILLYARD

Ready-To-Use

#802

Windo-Clean[®] +

Professional Strength Cleaner

CAUTION/CUIDADO

HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN
EYE IRRITANT -- MAY CAUSE NOSE AND THROAT IRRITATION

COMBUSTIBLE LIQUID OR VAPOR

KEEP OUT OF REACH OF CHILDREN

(See Manufacturer's Label for Additional Information)

Customer Affixed Label

2

HILLYARD
ARSENAL[®]

HILLYARD INDUSTRIES
St. Joseph, MO 64502 U.S.A.
Telephone: 816-233-1321
www.hillyard.com

DIRECTIONS FOR USE:

1. Use trigger sprayer, holding 6-8 inches from surface. Always work from bottom up. 2. Wipe dry with towel or cloth. 3. This product diluted at 6 ounces per gallon.

SPECIAL INSTRUCTIONS: For use only with Hillyard Arsenal Dilution System. When used on office machinery and data processing equipment (computers) or TV screens, always spray on paper towel or clean cloth and then wipe area to be cleaned. Never spray directly on any surface where working office machinery or computer parts would be exposed to this product. **DO NOT SPRAY ON FLAT WALL PAINTS OR HOT SURFACES.** Do not dispose of in storm drains or streams.

HMIS Rating: Health = 0, Flammability = 0, Reactivity = 0

CONTAINS: Water (CAS #7732-18-5); Butyl Cellosolve (CAS #111-76-2); Isopropyl Alcohol (CAS #67-63-0); Propylene Glycol Monomethyl Ether (CAS #107-98-2); Sulfated Ethoxylated Alcohol (CAS #27731-61-9).

FIRST AID: If swallowed, get medical attention immediately. In case of contact, immediately flush eyes or skin with plenty of water for 15 minutes. If irritation persists, get medical attention. Inhalation - If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

See Safety Data Sheet for additional information.

Label Reorder #HIL31621

CUIDADO

ES DAÑINO SI SE INGIERE O SI SE ABSORBE A TRAVES DE LA PIEL -- IRRITANTE DE LOS OJOS -- PUEDE CAUSAR IRRITACION DE LA NARIZ Y DE LA GARGANTA LIQUIDO O VAPOR COMBUSTIBLE

INSTRUCCIONES DE USO:

1. Use un atomizador, manteniéndolo alejado de 150 a 200 mm de la superficie. Siempre limpie de abajo hacia arriba. 2. Limpie y seque con una toalla o trapo. 3. Este producto diluido a 6 onzas por galón.

INSTRUCCIONES ESPECIALES: Use solo con Hillyard Arsenal Dilution System. Cuando se usa sobre el equipo de oficina o de procesamiento de datos (computadoras) o pantallas de televisión, siempre rocíe el producto en una toalla de papel o un trapo limpio y luego limpie el área a ser limpiada. Nunca rocíe el producto directamente sobre cualquier superficie en la cual las partes internas de funcionamiento de los equipos o computadora quedarían expuestas a este producto. **NO ROCIE SOBRE PINTURAS DE PAREDES OPACAS O SUPERFICIES CALIENTES.** No deseche el producto en los drenajes de agua de lluvia o en las corrientes de agua naturales.

Clasificación HMIS: Salud = 0, Inflamabilidad = 0, Reactividad = 0

CONTIENE: Agua (CAS #7732 18 5); Butil Cellosolve (CAS #111-76-2); Alcohol Isopropílico (CAS #67-63-0); Eter Monometilo De Propilen Glicol (CAS #107-98-2); Alcohol Etoxilado Sulfatado (CAS #27731-61-9).

PRIMEROS AUXILIOS: Si se ingiere, obtenga atención médica inmediatamente. En caso de contacto, inmediatamente lave los ojos o la piel con agua abundante por 15 minutos. Si la irritación persiste, obtenga atención médica. Si experimenta dificultades respiratorias, salga a un lugar con aire fresco. Si continúa sintiéndose mal, obtenga ayuda médica inmediatamente.

Ver la Hoja de Datos de Seguridad para obtener información adicional.

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS

(Consulte la etiqueta del fabricante para obtener información adicional.)

0115